INDUSTRIAL COMPONENT DATA

WML 8 (51X13)R 1488729 PHOENIX CONTACT Cable wrapping label, Roll, white, unlabeled, labelable with: THERMOM..

Brand: PHOENIX CONTACT | Manufacturer Part Number: WML 8 (51X13)R



Manufacturer	PHOENIX CONTACT
MPN / Reference	WML 8 (51X13)R
Catalog number	1488729
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-E6516CF33A
Generated	2026-11-18

Product Overview

Cable wrapping label, Roll, white, unlabeled, labelable with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting class: glued, cable diameter range: 4 ... 8.1 mm, cable diameter: <= 8.1 mm, usable area: 51 x 13 mm, Number of individual indexes: 1500
Cable Wrap Label, Roll, White, Unlabeled, Labelable with: THERMOMARKE.300 (D)/600 (D), THERMOMARK ROLL X1, THERMOMARK X1.2, THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLLMASTER 300/600, mounting class: glued, cable diameter range: 4 ... 8.1 mm, Number of individual indexes: 1500
Wire-wrap label, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: adhesive, cable diameter range: 4 ... 8.1 mm, cable diameter: <= 8.1 mm, lettering field size: 51 x 13 mm, Number of individual labels: 1500

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Technical dataProduct propertiesProduct type Conductor marking
Type Label
Marking
Number of individual labels 1500
Identification technology Thermal transfer for rolls

DimensionsWidth 50.8 mm
Length 38.1 mm
Material specificationsFoil strength 80 µm
Adhesive strength 21 µm
Adhesive Acrylic
Color white
Material PVC
Components Silicone-free
Cable/lineExternal cable diameter <= 8.1 mm
4 mm ... 8.1 mm
Environmental and real-life conditionsTest for substances that would hinder coating with paint or varnish
Result Test passed
Test for substances that would hinder coating with paint or varnish
Result Test passed
Scratch test for the determining scratch resistance
Specification DIN EN ISO 1518-1:2019-10 (following)
Requirements >= 5 N
Result Test passed
Tesafilm test
Specification DIN EN ISO 2409:2013 (following)
Result Test passed
UV resistance
Specification ISO 4892-2:2013-03 (following)
Result Test passed
Test duration 96 h
Temperature resistance
Specification ANSI/UL 969-2018:03 (following)
Test duration 240 h
Rating 100 °C (121 °C) Test passed
Specification ISO 175:2010 (following)
Test duration 168 h
IRM 901 Test passed
IRM 902 Test passed
Testing in a condensation changing climate in the presence of sulfur dioxide
Specification DIN 50018:2013-05
Result Test passed
Climate level AHT 1.0 S
Cycles 2
Salt spray test
Specification DIN EN 60068-2-11:2000-02
Result Test passed
Test duration 96 h
Ambient conditions
Ambient temperature (operation) -40 °C ... 80 °C
Ambient temperature (a...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WML 8 (51X13)R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.