INDUSTRIAL COMPONENT DATA

WML HF 7,5(25X13)R CUS 0830828 PHOENIX CONTACT Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: WML HF 7,5(25X13)R CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	WML HF 7,5(25X13)R CUS
Catalog number	0830828
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-06AB6FF4FD
Generated	2026-11-19

Product Overview

Cable marker
Cable marker, available: by lines, white, labelled according to customer specifications, mounting class: glued, cable diameter range: 4 ... 7.6 mm, cable diameter: <= 7.6 mm, usable area: 25x13mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data
Orderkey 0830828
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 197 (C-5-2013)
GTIN 4046356800846
Weight per Piece (excluding packing) 0.660 g
Custom tariff number 49119900
Country of origin DE (Germany)
Dimensions
Length (b) 36.5 mm
Width (a) 25.4 mm
Ambient conditions

Ambient temperature (operation) -40 °C ... 100 °C
Recommended storage conditions 21°C/50% relative humidity. Storage in the original packaging is recommended prior to processing.
General
Color white
Base element material Vinyl film
Type Label
Components free from silicone and halogen
Material Polyethylene
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels per row 3
Adhesive Acrylic
Printability Thermal transfer
Device 5146477 THERMOMARK ROLL
5146723 THERMOMARK ROLL X1
Ink ribbon 5145384 THERMOMARK-RIBBON 110
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Alternating condensation climate with SO2 test specification DIN 50018:2013-05
Climate level AHT 1.0 S
Cycles 2
Condensation test result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Marking mounting type ad...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WML HF 7,5(25X13)R CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.