INDUSTRIAL COMPONENT DATA

WMS-2 HF 12,7 (EX20)RL BU CUS 8199181 PHOENIX CONTACT Cable marker, blue: user-defined, mounting type: slide..

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMS-2 HF 12,7 (EX20)RL BU CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMS-2 HF 12,7 (EX20)RL BU CUS
Catalog number	8199181
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-E6B95EA509
Generated	2026-11-18

Product Overview

Cable marker, blue: user-defined, mounting type: slide on, lettering field size: max. 30 mm
Heat-shrink tubing, blue: customized, mounting class: sliding, usable surface: max. 30mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Cable marker, blue: user-defined, mounting type: slide on, lettering field size: max. 30 mm
Key Commercial Data
Orderkey 8199181
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4055626436753
Weight per Piece (excluding packing) 9.990 g
Custom tariff number 49119900
Country of origin PL (Poland)
Dimensions
Length (b) 80 mm
Width (a) 20 mm

General
Color blue
Type Shrink sleeve
Material Polyolefine
RoHS compliant Yes
Printing user-defined
Printability Thermal transfer
Device 5146477 THERMOMARK ROLL
5146723 THERMOMARK ROLL X1
5146231 THERMOMARK X1.2
5146147 THERMOMARK W2
0804501 THERMOMARK ROLLMASTER 300
0804663 THERMOMARK ROLLMASTER 600
Ink ribbon 5148007 THERMOMARK-RIBBON 110-WMTB HF
0801358 THERMOMARK-RIBBON 110-WMSU
0801360 THERMOMARK-RIBBON 64-WMSU
0803390 THERMOMARK-RIBBON 25-WMSU
0804661 TM-RIBBON 110 WH 100
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Procedure
Test duration 96 h
Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Procedure A
Test duration 96 h
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Test passed
Marking mounting type slide on
Oxygen index (DIN EN ISO 4589-2) 34.9 %
R22 HL 1 - HL 3
R23 HL 1 - HL 3
R24 HL 1 - HL 3
Standards and Regulations
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire prote...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMS-2 HF 12,7 (EX20)RL BU CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.