INDUSTRIAL COMPONENT DATA

# WMS-2 HF 25,4 (EX40)RL 0864106 PHOENIX CONTACT Shrink sleeve

**Brand: PHOENIX CONTACT | Manufacturer Part Number: WMS-2 HF 25,4 (EX40)RL**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | WMS-2 HF 25,4 (EX40)RL |
| Catalog number | 0864106 |
| Category | Cable coding system |
| Minimum order | 1 Pcs |
| Document ID | EO-3A13AD4378 |
| Generated | 2026-11-19 |

## Product Overview

Shrink sleeve
Heat-shrink tubing, Roll, white, unlabeled, labelable with: THERMOMARKE.300 (D)/600 (D), THERMOMARK ROLLMASTER 300/600, THERMOMARK ROLL X1, THERMOMARK ROLL, THERMOMARK ROLL 2.0, THERMOMARK W, THERMOMARK X1.2, UNDRILLED, MOUNTING CLASS: SLIP, CABLE DIAMETER RANGE: 12.7 ... 25.4 mm, usable area: 40x80000mm, length. Roll: 80 m

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > MS Material |

## Additional Product Information

Key Commercial Data
Orderkey 0864106
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 231 (C-3-2017)
GTIN 4055626070506
Weight per Piece (excluding packing) 99.990 g
Custom tariff number 39173200
Country of origin PL (Poland)
Dimensions
Length (b) 80 m

Width (a) 40 mm
Cable diameter 12.7 mm ... 25.4 mm
Ambient conditions
Ambient temperature (operation) -30 °C ... 105 °C
Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
General
Color white
Base element material polyolefine
Type Shrink sleeve
Components halogen-free
Material Polyolefine
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Printing without print
Printability Thermal transfer
Device 5146477 THERMOMARK ROLL
5146723 THERMOMARK ROLL X1
5146231 THERMOMARK X1.2
5146147 THERMOMARK W2
0804501 THERMOMARK ROLLMASTER 300
Ink ribbon 5148007 THERMOMARK-RIBBON 110-WMTB HF
0801358 THERMOMARK-RIBBON 110-WMSU
0801360 THERMOMARK-RIBBON 64-WMSU
0803390 THERMOMARK-RIBBON 25-WMSU
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMS-2 HF 25,4 (EX40)RL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.



Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.