
INDUSTRIAL COMPONENT DATA

WMS-2 HF 3,2 (15X5)RL YE CUS 0833215 PHOENIX CONTACT Shrink sleeve

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMS-2 HF 3,2 (15X5)RL YE CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMS-2 HF 3,2 (15X5)RL YE CUS
Catalog number	0833215
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-D7D9CEB8A0
Generated	2026-11-18

Product Overview

Shrink sleeve
Heat shrink tubing, Roll, yellow: custom, cut, mounting class: sliding, cable diameter range: 1.5 ... 3.2 mm, usable surface: 15 x 5 mm
Shrink sleeve, Roll, yellow: user-defined, Cut, mounting type: slide-on, cable diameter range: 1.5 ... 3.2 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Technical dataProduct propertiesProduct type Shrink sleeve printed
Area of application Railway industry
Type Shrink sleeve
Data management status
Article revision 01
Marking
Printing user-defined
Identification technology Thermal transfer for rolls
DimensionsWidth 5 mm
Length 15 mm
External dimensions
Outside diameter 1.5 mm ... 3.2 mm

Material specificationsColor yellow (RAL 1018)
Material Polyolefine
Base element material polyolefine
Shrink rate 2:1
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Components halogen-free
Shrink temperature > 90 °C
Cable/lineExternal cable diameter 1.5 mm ... 3.2 mm
Environmental and real-life conditionsTest for substances that would hinder coating with paint or varnish
Result Test passed
Test for substances that would hinder coating with paint or varnish
Result Test passed
Scratch test for the determining scratch resistance
Specification EN ISO 1518-1:2023 (following)
Requirements >= 5 N
Result Test passed
Tesafilm test
Specification DIN EN ISO 2409:2020-12 (following)
Result Test passed
UV resistance
Specification DIN EN ISO 4892-2:2021-11 (following)
Result Test passed
Test duration 96 h
Temperature resistance
Specification ANSI/UL 969-2018:03 (following)
Test duration 240 h
Rating 100 °C (121 °C) Test passed
Wipe resistance of inscriptions
Specification DIN EN 61010-1 (VDE 0411-01):2020-0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMS-2 HF 3,2 (15X5)RL YE CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.