
INDUSTRIAL COMPONENT DATA

WMS-2 HF 3,2 (60X5)RL YE CUS 0833219 PHOENIX CONTACT Shrink sleeve

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMS-2 HF 3,2 (60X5)RL YE CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMS-2 HF 3,2 (60X5)RL YE CUS
Catalog number	0833219
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-72257D9A0A
Generated	2026-11-18

Product Overview

Shrink sleeve
Heat shrink tubing, Roll, yellow: custom, cut, mounting class: sliding, cable diameter range: 1.5 ... 3.2 mm, usable surface: 60 x 5 mm
Heat Shrink Sleeve, Roll, Yellow: Customized, Cut, Mounting Class: Slip, Cable Diameter Range: 1.5 ... 3.2 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data
Orderkey 0833219
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4055626044866
Weight per Piece (excluding packing) 99.990 g
Custom tariff number 49119900
Country of origin DK (Denmark)
Dimensions
Length (b) 60 mm
Width (a) 5 mm
Cable diameter 1.5 mm ... 3.2 mm

Ambient conditions
Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
General
Color yellow
Base element material polyolefine
Type Shrink sleeve
Components halogen-free
Material Polyolefine
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Printing user-defined
Printability Thermal transfer
Device 5146477 THERMOMARK ROLL
5146723 THERMOMARK ROLL X1
5146231 THERMOMARK X1.2
5146147 THERMOMARK W2
0804501 THERMOMARK ROLLMASTER 300
Ink ribbon 5148007 THERMOMARK-RIBBON 110-WMTB HF
0801358 THERMOMARK-RIBBON 110-WMSU
0801360 THERMOMARK-RIBBON 64-WMSU
0803390 THERMOMARK-RIBBON 25-WMSU
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Marking mounting type slide on
Oxygen index (DIN EN ISO 4589-2) 34.9 %
R...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMS-2 HF 3,2 (60X5)RL YE CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.