INDUSTRIAL COMPONENT DATA

# WMS-2 HF 6,4 (EX10)R BU CUS 8199180 PHOENIX CONTACT Cable marker

**Brand: PHOENIX CONTACT | Manufacturer Part Number: WMS-2 HF 6,4 (EX10)R BU CUS**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | WMS-2 HF 6,4 (EX10)R BU CUS |
| Catalog number | 8199180 |
| Category | Cable coding system |
| Minimum order | 1 Pcs |
| Document ID | EO-B122C13AA3 |
| Generated | 2026-11-18 |

## Product Overview

Cable marker
Heat-shrink tubing, blue: customized, mounting class: sliding, usable surface: max. 30mm
Heat Shrink Sleeve, Blue: Customized, Mounting Class: Sliding

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > CABINET add-on |

## Additional Product Information

Key Commercial Data
Orderkey 8199180
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4055626436746
Weight per Piece (excluding packing) 9.990 g
Custom tariff number 49119900
Country of origin DE (Germany)
Dimensions
Length (b) 25 mm
Width (a) 6.4 mm
Ambient conditions
Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is

recommended.
General
Color blue
Type Shrink sleeve
Material Polyolefine
RoHS compliant Yes
Printing user-defined
Printability Thermal transfer
Device 5146477 THERMOMARK ROLL
5146723 THERMOMARK ROLL X1
5146231 THERMOMARK X1.2
5146147 THERMOMARK W2
0804501 THERMOMARK ROLLMASTER 300
0804663 THERMOMARK ROLLMASTER 600
Ink ribbon 5148007 THERMOMARK-RIBBON 110-WMTB HF
0801358 THERMOMARK-RIBBON 110-WMSU
0801360 THERMOMARK-RIBBON 64-WMSU
0803390 THERMOMARK-RIBBON 25-WMSU
0804661 TM-RIBBON 110 WH 100
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Procedure
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Procedure A
Test duration 96 h
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Marking mounting type slide on
Oxygen index (DIN EN ISO 4589-2) 34.9 %
R22 HL 1 - HL 3
R23 HL 1 - HL 3
R24 HL 1 - HL 3
Stan...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMS-2 HF 6,4 (EX10)R BU CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.