INDUSTRIAL COMPONENT DATA

WMTB-AL (40X15) CUS 0830526 PHOENIX CONTACT Aluminum label

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMTB-AL (40X15) CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMTB-AL (40X15) CUS
Catalog number	0830526
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-87A6728875
Generated	2026-11-19

Product Overview

Aluminum label
Aluminium sign, available: by piece, aluminium colour, labelled according to customer's instructions, mounting class: Mounting with cable ties, cable diameter: > 4.6 mm, usable area: 40 x 15 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data
Orderkey 0830526
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 161 (C-5-2013)
GTIN 4046356718981
Weight per Piece (excluding packing) 2.070 g
Custom tariff number 76169990
Country of origin DE (Germany)
Dimensions
Length (b) 59 mm
Width (a) 15 mm
Ambient conditions

Recommended storage conditions 5°C to 25°C
General
Color aluminum color
Type Roll
Components free from silicone, halogen, and cadmium
Material Aluminum
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Printability UV LED technology
Device 5147999 BLUEMARK CLED
5146662 BLUEMARK CLED-FLUID-CARTR.
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Alternating condensation climate with SO2 test specification following DIN 50018:2013-05
Climate level AHT 1.0 S
Cycles 2
Condensation test result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Marking mounting type Assembly with cable binders
Min. cross section 16 mm²
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Classifications
eCl@ss 4.024190218eCl@ss 4.124190218eCl@ss 5.027141137eCl@ss 5.127400400eCl@ss 6.027400400eCl@ss 7.027400401eCl@ss 8.02...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMTB-AL (40X15) CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.