INDUSTRIAL COMPONENT DATA

WMTB HF-HP (40X12)R OG 1525868 PHOENIX CONTACT Cable marker, Roll, orange, unlabeled, labelable with: THERMO..

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMTB HF-HP (40X12)R OG



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMTB HF-HP (40X12)R OG
Catalog number	1525868
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-A4E576932E
Generated	2026-11-18

Product Overview

Cable marker, Roll, orange, unlabeled, labelable with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting class: Mounting with cable tie, cable diameter: >= 6 mm, useful surface: 40 x 12 mm, Number of individual indexes: 1000
Cable Marker
Cable marker, Roll, orange, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: Assembly with cable ties, cable diameter: >= 6 mm, lettering field size: 40 x 12 mm, Number of individual labels: 1000

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Technical dataProduct propertiesProduct type Conductor marking
Type Roll
Area of application Railway industry
Marking
Number of individual labels 1000

Identification technology Thermal transfer for rolls
DimensionsWidth 12 mm
Length 40 mm
Material specificationsColor orange
Material Polyolefine
Base element material polyolefine
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Cable/lineExternal cable diameter >= 6 mm
Environmental and real-life conditionsTest for substances that would hinder coating with paint or varnish
Result Test passed
Scratch test for the determining scratch resistance
Specification DIN EN ISO 1518-1:2019-10 (following)
Requirements >= 5 N
Result Test passed
Tesafilm test
Specification DIN EN ISO 2409:2013 (following)
Result Test passed
UV resistance
Specification ISO 4892-2:2013-03 (following)
Result Test passed
Test duration 96 h
Specification IEC 60068-2-2:2007-07
Result Test passed
Duration 96 h
Temperature for testing 105 °C
Testing in a condensation changing climate in the presence of sulfur dioxide
Specification DIN 50018:2013-05
Result Test passed
Climate level AHT 1.0 S
Cycles 2
Salt spray test
Specification DIN EN 60068-2-11:2000-02
Result Test passed
Test duration 96 h
Ambient conditions
Ambient temperature (operation) -55 °C ... 105 °C
Recommended ambient temperature (storage/transport) 10 °C ....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMTB HF-HP (40X12)R OG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.