INDUSTRIAL COMPONENT DATA

WMTW (23X4)R YE CUS 0831006 PHOENIX CONTACT Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMTW (23X4)R YE CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMTW (23X4)R YE CUS
Catalog number	0831006
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-361CCB079E
Generated	2026-11-18

Product Overview

Cable marker
Cable marker, available: by lines, yellow, labeled according to customer specifications, mounting class: plugged in, cable diameter range: 1.5 ... 35 mm, usable area: 23 x 4 mm
Cable marker, can be ordered: by line, yellow, labeled according to customer specifications, mounting type: plug in, cable diameter range: 1.5 ... 35 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Technical dataProduct propertiesProduct type Labeled conductor marker
Data management status
Article revision 01
Marking
Number of individual labels per row 1
MountingMounting type plug in
Material specificationsRoHS compliant yes
Foil strength 250 µm
Color yellow (RAL 1018)
Material Polyolefine
Environmental and real-life conditionsTest for substances that would hinder coating with paint or varnish

Result Test passed
Scratch test for the determining scratch resistance
Specification DIN EN ISO 1518-1:2011 (following)
Requirements >= 5 N
Result Test passed
Tesafilm test
Specification DIN EN ISO 2409:2013 (following)
Result Test passed
UV resistance
Specification ISO 4892-2:2013-03 (following)
Result Test passed
Test duration 96 h
Temperature resistance
Specification ANSI/UL 969-2018:03 (following)
Test duration 240 h
Rating 80 °C (105 °C) Test passed
Wipe resistance of inscriptions
Specification DIN EN 61010-1 (VDE 0411-1):2011-07
DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Isopropyl
[CAS No. 67-63-0] Test passed
n-Hexane
[CAS No. 110-54-3] Test passed
Water + Petroleum ether
[CAS No. 64742-82-1] Test passed
Sodium hydroxide 0.1 mol/l
[CAS No. 1310-73-2] Test passed
Specification ISO 175:2010 (following)
Test duration 168 h
IRM 901 Test passed
IRM 902 Test passed
Testing in a condensation changing climate in the presence of sulfur dioxide
Specification DIN 50018:2013-05
Result Test passed
Climate level AHT 1.0 S
Cycles 2
Salt spray test
Specification DIN EN 60068-2-11:2000-...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMTW (23X4)R YE CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.