
INDUSTRIAL COMPONENT DATA

ZB 5,8:UNBEDRUCKT 2715209 PHOENIX CONTACT Zack marker strip

Brand: PHOENIX CONTACT | Manufacturer Part Number: ZB 5,8:UNBEDRUCKT



Manufacturer	PHOENIX CONTACT
MPN / Reference	ZB 5,8:UNBEDRUCKT
Catalog number	2715209
Category	Labelling for terminal block
Minimum order	10 Pcs
Document ID	EO-3BECB7FBF3
Generated	2026-11-19

Product Overview

Zack marker strip
Zack tape strip, Strips, white, unlabeled, labelable with: PLOTMARK, CMS-P1-PLOTTER, mounting type: interlock, for terminal width: 5.8 mm, useful surface: 5.75x10.5mm, Number of individual indexes: 10
Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: latching, for terminal block width: 5.8 mm, Number of individual labels: 10, text field height: 10.5 mm, text field width: 5.75 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Technical dataNotesGeneral Can be labeled with CMS
Product propertiesProduct type Terminal marking
Pitch 5.8 mm
Type high
Data management status
Article revision 01
Marking
Number of individual labels 10
Number of individual labels per row 10
Number of marker strips 10
DimensionsWidth 5.8 mm

Text field width 5.75 mm
Text field height 10.50 mm
Pitch 5.8 mm
Material specificationsColor white (RAL 9010)
Material PA
Flammability rating according to UL 94 V2
Components free from silicone and halogen
Environmental and real-life conditionsUV resistance
Specification ISO 4892-2:2013-03 (following)
Wipe resistance of inscriptions
Specification DIN EN 61010-1 (VDE 0411-1):2011-07
DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Ambient conditions
Ambient temperature (operation) -40 °C ... 100 °C
Recommended ambient temperature (storage/transport) 23 °C
Recommended humidity (storage/transport) 50 %
Standards and regulationsWipe resistance DIN EN 61010-1 (VDE 0411-1)
DIN VDE 0611
MountingMounting type latching

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ZB 5,8:UNBEDRUCKT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.