INDUSTRIAL COMPONENT DATA

ZEC 1,0/ 4-ST-3,5 C1 R1,4 AU 1712458 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: ZEC 1,0/ 4-ST-3,5 C1 R1,4 AU



Manufacturer	PHOENIX CONTACT
MPN / Reference	ZEC 1,0/ 4-ST-3,5 C1 R1,4 AU
Catalog number	1712458
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-180048C76E
Generated	2026-11-19

Product Overview

Printed-circuit board connector
Direct connector for printed circuit board, nominal section: 1 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 200 V, contact surface: Gold, contact type: Female, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: ZEC 1.0/.. -ST, pitch: 3.5 mm, connection type: Spring connection, mounting: Direct plug-in connection technique, connection direction conductor/printed circuit board: 0 °, plug-in system: ZEC, locking: Snap lock, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1712458
Packing unit 50 pc
Minimum order quantity 50 pc
GTIN 4046356084109
Weight per Piece (excluding packing) 4.840 g
Custom tariff number 85366930
Country of origin GR (Greece)
Dimensions
Pitch 3.5 mm

Dimension a 10.5 mm
General
Range of articles ZEC 1,0/..-ST
Number of positions 4
Connection method Spring-cage connection
Rated voltage (III/3) 160 V
Connection in acc. with standard EN-VDE
Nominal current IN 8 A
Nominal cross section 1 mm²
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 1 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 1 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 1 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 0.75 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 16
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. 0.5 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. 0.5 mm²
Minimum AWG according to UL/CUL 26
Maximum AWG according to UL/CUL 16
Standards and Regulations
Connection in acc. with standard EN-VDE
CUL
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ZEC 1,0/ 4-ST-3,5 C1 R1,4 AU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.