INDUSTRIAL COMPONENT DATA

SAC-5P-MS/ 5,0-100/FS SCO OBS 1562152 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-MS/ 5,0-100/FS SCO OBS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-MS/ 5,0-100/FS SCO OBS
Catalog number	1562152
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-3F58F2C79B
Generated	2026-11-19

Product Overview

Sensor/actuator cable
Sensor/actuator cable, 5-pole, M12 SPEEDCON straight male connector, coding: A, to M12 SPEEDCON straight connection female, coding: A, cable length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1562152
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
GTIN 4046356292016
Weight per Piece (excluding packing) 259.120 g
Custom tariff number 85444290
Country of origin PL (Poland)
Dimensions
Length of cable 5 m
Ambient conditions
Degree of protection IP65

IP67
IP68
General
Rated current at 40°C 4 A
Rated voltage 48 V AC
60 V DC
Number of positions 5
Insulation resistance >= 10 M?
Coding A - standard
Status display No
Overvoltage category II
Degree of pollution 3
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type PUR/PVC gray
Cable type (abbreviation) 100
Cable abbreviation LiYY-11Y
Conductor cross section 0.34 mm²
AWG signal line 22
Conductor structure signal line 42x 0.10 mm
Core diameter including insulation 1.5 mm ±0.05 mm
Thickness, insulation >= 0.3 mm (Core insulation)
>= 0.38 mm (Outer cable sheath)
approx. 0.35 mm (Inner sheath)
Wire colors brown, white, blue, black, green-yellow
Overall twist 5 wires around filler to the core
External sheath, color gray RAL 7001
External cable diameter D 5.9 mm ±0.2 mm
Smallest bending radius, fixed installation 29.5 mm
Smallest bending radius, movable installation 59 mm
N...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-MS/ 5,0-100/FS SCO OBS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.