
INDUSTRIAL COMPONENT DATA

DFMC 1,5/20-ST-3,5-LRBKBDMC-21 1711798 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFMC 1,5/20-ST-3,5-LRBKBDMC-21



Manufacturer	PHOENIX CONTACT
MPN / Reference	DFMC 1,5/20-ST-3,5-LRBKBDMC-21
Catalog number	1711798
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-42ABEB82B0
Generated	2026-11-19

Product Overview

Printed-circuit board connector
Connector for printed circuit board, nominal section: 1.5 mm², color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Female, number of potentials: 40, number of rows: 2, number of poles: 20, number of connections: 40, article family: DFMC 1.5/.. -ST-LR, pitch: 3.5 mm, connection type: Push-in spring connection, driver/printed circuit board connection direction: 0°, plug-in system: COMBICON DFMC 1.5, lock: Snap lock, fixing type: Lock & Release puller lever, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1711798
Packing unit 1
GTIN 4055626266404
Custom tariff number 85366990
Dimensions
Length [l] 23.35 mm
Width [w] 76.9 mm
Height [h] 13.25 mm
Pitch 3.5 mm

Dimension a 66.5 mm
General
Range of articles DFMC 1,5/..-ST-LR
Number of positions 20
Connection method Push-in spring connection
Insulating material group I
Rated voltage (III/2) 160 V
Nominal current IN 8 A
Nominal cross section 1.5 mm²
Flammability rating according to UL 94 V0
Specifications for ferrules
Recommended crimping pliers 1212034 CRIMPFOX 6
Ferrules without insulating collar, according to DIN 46228-1 Cross section: 0.25 mm²; Length: 5 mm ... 7 mm
Cross section: 0.34 mm²; Length: 7 mm
Cross section: 0.5 mm²; Length: 8 mm ... 10 mm
Cross section: 0.75 mm²; Length: 8 mm ... 10 mm
Cross section: 1 mm²; Length: 8 mm ... 10 mm
Cross section: 1.5 mm²; Length: 10 mm
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440309eCl@ss 8.027440309eCl@ss 9.027440309
ETIM 5.0EC002638ETIM 6.0EC002638

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFMC 1,5/20-ST-3,5-LRBKBDMC-21 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.