

INDUSTRIAL COMPONENT DATA

ZFK4DSA 1,5-5,08-11 1100962 PHOENIX CONTACT Terminal for printed circuit board, nominal current: 12 A, pitch..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ZFK4DSA 1,5-5,08-11

PRODUCT IMAGE\nNOT
AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	ZFK4DSA 1,5-5,08-11
Catalog number	1100962
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-5050F82561
Generated	2026-09-30

Product Overview

Terminal for printed circuit board, nominal current: 12 A, pitch: 5,08 mm, number of poles: 11, type of connection: spring clamp, mounting: Soldering by wave direction for connection conductor/pcb: 45 °, color: green
PCB terminal, nominal current: 12 A, nominal voltage (III/2): 400 V, nominal cross-section: 1.5 mm², number of rows: 4, number of poles per row: 11, article family: ZFK4DS(A) 1.5, pitch: 5.08 mm, connection type: Spring connection, mounting: Wave soldering, conductor/PCB connection direction: 45°, Color: Green, Pin Arrangement: Linear Pin Arrangement, Pin Length [P]: 3.4mm, Number of Solder Pins by Potential: 1, Packing Type: Boxed Packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ZFK4DSA 1,5-5,08-11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.