


INDUSTRIAL COMPONENT DATA

ZFK4DSA 1,5-5,08- 4 GY BD:13-4 1751998 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: ZFK4DSA 1,5-5,08- 4 GY BD:13-4



Manufacturer	PHOENIX CONTACT
MPN / Reference	ZFK4DSA 1,5-5,08- 4 GY BD:13-4
Catalog number	1751998
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-7D70700C51
Generated	2026-09-22

Product Overview

PCB terminal block

Terminal block for printed circuit board, rated current: 12 A, dimensioning voltage (III/2): 400 V, nominal cross-section: 1.5 mm², Number of potentials: 16, Number of rows: 4, Number of poles per row: 4, article family: ZFK4DS(A) 1.5, pitch: 5.08 mm, connection type: Spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 45 °, color: gray, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.4 mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1751998

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356335263

Weight per Piece (excluding packing) 30.460 g

Custom tariff number 85369010

Country of origin PL (Poland)

Dimensions

Length [L] 42.4 mm

Pitch 5.08 mm

Dimension a 15.24 mm

Width [w] 21.32 mm

Height 48 mm

Height [h] 51.2 mm

Solder pin [P] 3.4 mm

Hole diameter 1.3 mm

General

Range of articles ZFK4DS(A) 1,5

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 400 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current I_N 12 A

Nominal cross section 1.5 mm²

Maximum load current 12 A

Insulating material PA

Contact material Sn

Solder pin surface

Flammability rating according to UL 94 V0

Internal cylindrical gage A1

Stripping length 7.5 mm

Number of positions 4

Connection data

Conductor cross section AWG min. 24

Conductor cross section AWG max. 14

Standards and Regulations

Connection in acc. with standard EN-VDE

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027141111eCl@ss 4.127141109eCl@ss 5.027141190eCl@ss 5.127261100eCl@ss 6.027261100eCl@ss

7.027440401eCl@ss 8.027440401eCl@ss 9.027440401

ETIM 3.0EC001121ETIM 4.0EC002643ETIM...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ZFK4DSA 1,5-5,08- 4 GY BD:13-4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.