


INDUSTRIAL COMPONENT DATA

ZFKDSA 1,5C-5,0-10 1988574 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: ZFKDSA 1,5C-5,0-10



Manufacturer	PHOENIX CONTACT
MPN / Reference	ZFKDSA 1,5C-5,0-10
Catalog number	1988574
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-19AE328C36
Generated	2026-09-29

Product Overview

PCB terminal block

Terminal block for printed circuit board, rated current: 16 A, rated voltage (III/2): 400 V, rated cross-section: 1.5 mm², number of potentials: 10, number of rows: 1, number of poles per row: 10, article family: ZFKDS(A) 1.5C, pitch: 5 mm, connection type: Spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 45 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 2, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1988574

Packing unit 50 pc

Minimum order quantity 50 pc

GTIN 4017918938390

Weight per Piece (excluding packing) 9.760 g

Custom tariff number 85369010

Country of origin PL (Poland)

Dimensions

Length [L] 14.1 mm

Pitch 5 mm

Dimension a 45 mm

Width [w] 41 mm

Height 12.75 mm

Height [h] 16.25 mm

Solder pin [P] 3.5 mm

Pin spacing 5.08 mm

Hole diameter 1.1 mm

General

Range of articles ZFKDS(A) 1,5C

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 400 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current I_N 16 A

Nominal cross section 1.5 mm²

Maximum load current 16 A

Insulating material PA

Solder pin surface

Flammability rating according to UL 94 V0

Internal cylindrical gage A1

Stripping length 7 mm

Number of positions 10

Connection data

Conductor cross section AWG min. 24

Conductor cross section AWG max. 14

2 conductors with same cross section, stranded min. 0.14 mm²

2 conductors with same cross section, stranded max. 0.5 mm²

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027141109eCl@ss 4.127141109eCl@ss 5.027141190eCl@ss 5.127261100eCl@ss 6.027261100eCl@ss 7....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ZFKDSA 1,5C-5,0-10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.