

INDUSTRIAL COMPONENT DATA

THERMOMARK GO.K SET 1184148 PHOENIX CONTACT

Portable thermal transfer printer for marking materials in cartr..

Brand: PHOENIX CONTACT | Manufacturer Part Number: THERMOMARK GO.K SET



Manufacturer	PHOENIX CONTACT
MPN / Reference	THERMOMARK GO.K SET
Catalog number	THERMOMARK GO.K SET
Category	Printer/scanner/copier
Minimum order	1 unit
Document ID	EO-227A76AE01
Generated	2026-08-01

Product Overview

Portable thermal transfer printer for marking materials in cartridge format, including accessories in the practical case of the tried-and-tested L-BOXX system. The printer can print materials in endless format up to a media width of 24 mm.

Mobile thermal transfer printer for marking materials in cartridge format, including accessories in a practical case. The printer can print materials in continuous format up to a material width of 24 mm.

STRUCTURED PRODUCT DATA

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Printer (EF002805)	Yes
Scanner (EF005223)	No
Fax (EF004680)	No
Photocopier (EF004853)	No
Print process (EF000727)	Thermal
Duplex printing (EF009717)	No
Parallel connection (EF005162)	No
Serial connection (EF005273)	No
Height (EF000040)	69 mm
Width (EF000008)	98 mm
Depth (EF000049)	230 mm

Classification & Catalog Path

Catalog path

PHOENIX CONTACT > MS devices / software

Additional Product Information

Key Commercial Data

Orderkey 1184148

Packing unit 1 pc

GTIN 4063151223533

Weight per Piece (excluding packing) 1.000 g

Custom tariff number 84433210

Country of origin CN (China)

General

Connection data

Set Items

Dimensions

Environmental Product Compliance

Classifications

General

Interface USB

Weight 3390 g

Back to topDimensions

Length 230 mm

Height 69 mm

Width 98 mm

Back to topConnection data

Minimum voltage 100 V AC

Max. voltage 240 V AC

Additional text 50 Hz ... 60 Hz

Back to topEnvironmental Product Compliance

REACH SVHC Lead 7439-92-1

Back to topArticles in set

Thermal transfer printer THERMOMARK GO.K 1184146

Mobile thermal transfer printer for marking materials in cartridge format. The printer can print materials in continuous format up to a material width of 24 mm.

DownloadsTechnical data

Battery THERMOFOX/ACCU 0805009

Battery for mobile operation of the THERMOMARK GO and THERMOMARK GO.K / THERMOFOX printers.

DownloadsTechnical data

Power supply unit THERMOFOX/ADAPTER 0805010

Power supply unit incl. 4 adapters for operation of the THERMOMARK GO and THERMOMARK GO.K / THERMOFOX....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / THERMOMARK GO.K SET with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.