

INDUSTRIAL COMPONENT DATA

REL-FO/LRC-230AC/2X21/MS 1308330 PHOENIX CONTACT

Plug-in miniature relay with mechanical switching position ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: REL-FO/LRC-230AC/2X21/MS



Manufacturer	PHOENIX CONTACT
MPN / Reference	REL-FO/LRC-230AC/2X21/MS
Catalog number	1308330
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-3CB3560D56
Generated	2026-08-01

Product Overview

Plug-in miniature relay with mechanical switching position indicator, FASTON connection, 2 switched contacts, status indication: LED (yellow), RC module, Input voltage: 230 V AC
REL-FO/LRC-230AC/2X21/MS - Single Relay

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays
--------------	-------------------------------------

Additional Product Information

Technical dataNotesGeneral They should not be used to separate SELV/PELV electrical circuits from other electrical circuits, as safe separation is not guaranteed. (valid for optocoupler variants)

General The outputs are not suitable for connecting different phases.

General Protection against accidental contact of the article (with voltages > 25 V AC/60 V DC) must be ensured by the system manufacturer. This is an assembly device without protection against direct contact.

Item PropertiesProduct Type Individual relay

Product Family ESSENTIAL edition

Operating Mode Working time 100%

Mechanical service life approx. 3x 10⁷operations

Relay Type Electromechanical relay

Insulation Properties: Leak Lines and Air Gaps Between Circuits

Isolation Basic Insulation

Surge Category II

Degree of pollution 3

Electrical PropertiesMaximum Dissipated Power with Nominal Condition 1 W

Test Voltage (Winding/Contact) 5 kVEff(50 Hz, 1 min., winding/contact)

Test Voltage (Commutator/Commutator) 3 kVEff(50 Hz, 1 min., switch/switch)

Test Voltage () 1 kVEff(50 Hz, 1 min., open contact)

Creepage lines and air gaps between circuits

Sizing Insulation Voltage 250 V AC

Dimensioning Transient Voltage 2.5 kV

Input dataArousal Side

Nominal Input Voltage UN 230 V AC

Input Voltage Range 184 V AC ... 253 V AC

Mains Frequency 50/60 Hz

Drive switching behavior monostable

Drive (polarity) bipolar

Typical Input Current to UN 4.5 mA (50 Hz)

Input Dissipated Power with UN 1 W

Typical Reaction Time 2 ms ... 15 ms

Typical....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / REL-FO/LRC-230AC/2X21/MS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.