

INDUSTRIAL COMPONENT DATA

SACC-CI-M12FST-4CON-L180 THR SH SP 1421316 PHOENIX CONTACT Sample set

Brand: PHOENIX CONTACT | Manufacturer Part Number: 1421316



Manufacturer	PHOENIX CONTACT
MPN / Reference	1421316
Catalog number	SACC-CI-M12FST-4CON-L180 THR SH SP
Category	Contact insert for circular connectors
Minimum order	1 Pcs
Document ID	EO-4490495616
Generated	2026-08-05

Product Overview

Sample set

Sample Set, Universal, 4-Pole, Female Connection, Straight, M12, T - Power, Printed Circuit Board Mounting, THR Welding Connection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Sample set, Universal, 4-position, Socket, straight, M12, T power, PCB mounting, THR solder connection

Key Commercial Data

Orderkey 1421316

Packing unit 1

GTIN 4055626257815

Custom tariff number 85389099

Environmental Product Compliance

REACH SVHC

Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 6.027279200eCl@ss 7.027440103eCl@ss 8.027440103eCl@ss 9.027440102

ETIM 5.0EC002061ETIM 6.0EC002061

UNSPSC 13.239121413

ETIM for 1421316 Connectors (EC002635)

Feature Name

Feature Value

Contact type (EF001587)

Other

Number of data contacts (EF012232)

0

Number of power contacts (EF012216)

0

Number of control contacts (EF012217)

4

Type of housing (EF006980)

Straight

Rated current In (EF008250)

12 A

Ambient temperature (EF002386)

-25 °C

Rated voltage (EF000228)

60 V

Over voltage category (EF006785)

III

Pollution degree (EF006786)

3

Material of contact surface (EF004020)

Gold

Housing material (EF001596)

Plastic

Type of locking (EF000208)

Other

Inflammability class of insulation material according to UL94 (EF002521)

V0

With protective conductor (EF007468)

No

Degree of protection (IP), mounted (EF007466)

IP67

Min. number of insertion cycles (EF012212)

100

Screened (EF000881)

Yes

With status indication (EF001602)

No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / 1421316 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.