

INDUSTRIAL COMPONENT DATA

MINI MCR-SL-IDS-I-I 2905577 PHOENIX CONTACT Output signal conditioner

Brand: PHOENIX CONTACT | Manufacturer Part Number: MINI MCR-SL-IDS-I-I



Manufacturer	PHOENIX CONTACT
MPN / Reference	MINI MCR-SL-IDS-I-I
Catalog number	2905577
Category	Isolation amplifier
Minimum order	1 Pcs
Document ID	EO-38D60C310F
Generated	2026-08-06

Product Overview

Output signal conditioner

3-way output splitter amplifiers for 0/4 ... 20 mA signals from the control system for a load that is in the field simultaneously with 3-way separation between input, output and screw connection supply

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > INTERFACE Components (IF)**

Additional Product Information

Key Commercial Data

Orderkey 2905577

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 100 (C-7-2015)

GTIN 4046356966290

Weight per Piece (excluding packing) 87.700 g

Custom tariff number 85437090

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 6.2 mm

Height 93.1 mm

Depth 102.5 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 60 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Input data

Number of inputs 1

Current input signal 4 mA ... 20 mA

0 mA ... 20 mA

Max. input current 20 mA

Input voltage limitation < 2 V (20 mA)

Output data

Output name Current output

Number of outputs 1

Current output signal 4 mA ... 20 mA

0 mA ... 20 mA

Load/output load current output <= 800 ? (at 20 mA)

Ripple < 20 mVrms

Transmission Behavior 1:1 to input signal

Power supply

Nominal supply voltage 24 V DC

Supply voltage range 19.2 V DC ... 30 V DC (The DIN rail bus connector (ME 6,2 TBUS-2 1,5/5-ST-3,81 GN, Order No. 2869728) can be used to bridge the supply voltage. It can be snapped onto a 35 mm DIN rail according to EN 60715))

Power consumption < 600 mW (at 24 V DC)

Connection data

Connection method Screw connection

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section AWG min. 26

Conductor cross section AWG max. 12

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MINI MCR-SL-IDS-I-I with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.