

INDUSTRIAL COMPONENT DATA

PLC-BSC- 24UC/ 1/ACT 2982799 PHOENIX CONTACT Relay base

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-BSC-24UC/ 1/ACT



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-BSC-24UC/ 1/ACT
Catalog number	2982799
Category	Relay socket
Minimum order	1 Pcs
Document ID	EO-FB5B1ECD38
Generated	2026-08-02

Product Overview

Relay base

6.2 mm PLC base terminal block for output functions with screw connection, without relay or solid-state relay equipment, for mounting on NS 35/7.5 rail, with load return line (BB) connection, 1 closing contact, input voltage 24 V AC/DC

6.2 mm PLC basic terminal block for output functions with screw connection, without relay or solid-state relay, for mounting on DIN rail NS 35/7,5, with load return line connection (BB), 1 N/O contact, input voltage 24 V AC/DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays
--------------	-------------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Relay socket

Product family PLC-INTERFACE

Application Output function

Operating mode 100% operating factor

Compatible components Miniature relay, REL-MR-24DC/21, REL-MR-24DC/21AU; miniature optocoupler, OPT-24DC/24DC/2, OPT-24DC/48DC/100, OPT-24DC/230AC/1

Data management status

Article revision 06

Insulation characteristics

Pollution degree 3

Input dataNominal input voltage UN 24 V AC/DC

The nominal voltage of the plug-on electromechanical relay or solid-state relay (see necessary accessories) deviates from the nominal input voltage of the base with integrated upstream circuit

Protective circuit Bridge rectifier

Nominal input voltage UN 24 V AC/DC

The nominal voltage of the plug-on electromechanical relay or solid-state relay (see necessary accessories) deviates from the nominal input voltage of the base with integrated upstream circuit

Relay assembly

Rated control circuit supply voltage US 24 V AC/DC

Voltage range with reference to US 0.8 ... 1.2

Typical input current at UN 15.6 mA (50 Hz)

8.5 mA (60 Hz)

Typical response time 5 ms

Typical release time 30 ms

Operating voltage display Yellow LED

Protective circuit Bridge rectifier; Bridge rectifier

Optocoupler assembly

Rated control circuit supply voltage US 24 V AC/DC

Voltage range with reference to US 0.8 ... 1.2

Typical input current at UN 15 mA (50 Hz)

8.3 mA (60 Hz)

Typical response time 10 ms

Typical release time 20 ms

Operating voltage display Yellow LED

Protective circuit B...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-BSC-24UC/ 1/ACT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.