

INDUSTRIAL COMPONENT DATA

PLC-OPT-110DC/ 24DC/3RW 2900380 PHOENIX CONTACT

Solid-state relay module

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-OPT-110DC/ 24DC/3RW



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-OPT-110DC/ 24DC/3RW
Catalog number	2900380
Category	Optocoupler
Minimum order	1 Pcs
Document ID	EO-C499B959E5
Generated	2026-08-04

Product Overview

Solid-state relay module

PLC-INTERFACE for railway applications, consisting of base terminal block with push-in connection and integrated miniature solid-state relay, range: 0.7 x UN to 1.25 x UN, temperature range: -25 °C to +70 °C, 1 closing contact, input: 110 V DC, output: 3-33 V DC/3 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays
--------------	-------------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2900380

Packing unit 10 pc

Note Made to Order (non-returnable)

Catalog page Page 415 (C-5-2017)

GTIN 4046356508940

Weight per Piece (excluding packing) 29.690 g

Custom tariff number 85364900

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 6.2 mm

Height 80 mm

Depth 86 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 70 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Degree of protection IP20

Input data

Nominal input voltage UN 110 V DC

Input voltage range in reference to UN 0.7 ... 1.25 ($t < 1 \text{ s} = 0.6 \dots 1.4 \times \text{UN}$)

Input voltage range 77 V DC ... 137.5 V DC

Switching threshold "0" signal in reference to UN ≤ 0.3

Switching threshold "1" signal in reference to UN ≥ 0.6

Typical input current at UN 3 mA

Typical response time 80 μs

Typical turn-off time 600 μs

Operating voltage display Yellow LED

Type of protection Reverse polarity protection

Protective circuit/component Polarity protection diode

Transmission frequency 100 Hz

Power dissipation for nominal condition 0.33 W

Output data

Output nominal voltage 24 V DC

Output voltage range 3 V DC ... 33 V DC ($t < 1 \text{ s} = 1.40 \times \text{UN}$)

Limiting continuous current 3 A (see derating curve)

Surge voltage protection $> 33 \text{ V DC}$

Voltage drop at max. limiting continuous current $< 200 \text{ mV}$

Output circuit 2-wire, floating

Type of protection Reverse polarity protection

Surge protection

Protective....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-OPT-110DC/ 24DC/3RW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.