

INDUSTRIAL COMPONENT DATA

PLC-OPT- 48DC/110DC/3RW 2900393 PHOENIX CONTACT

Solid-state relay module

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-OPT-48DC/110DC/3RW



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-OPT-48DC/110DC/3RW
Catalog number	2900393
Category	Optocoupler
Minimum order	1 Pcs
Document ID	EO-9531D8A839
Generated	2026-08-03

Product Overview

Solid-state relay module

PLC-INTERFACE for railway applications, consisting of base terminal block with push-in connection and integrated miniature solid-state relay, range: 0.7 x UN to 1.25 x UN, temperature range: -25 °C to +70 °C, 1 closing contact, input: 48 V DC, output: 12-140 V DC/3 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays
--------------	-------------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2900393

Packing unit 10 pc

Note Made to Order (non-returnable)

Catalog page Page 415 (C-5-2017)

GTIN 4046356508988

Weight per Piece (excluding packing) 31.890 g

Custom tariff number 85364190

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 6.2 mm
Height 80 mm
Depth 86 mm
Ambient conditions
Ambient temperature (operation) -25 °C ... 70 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Degree of protection IP20
Input data
Nominal input voltage UN 48 V DC
Input voltage range in reference to UN 0.7 ... 1.25 ($t < 1 \text{ s} = 0.6 \dots 1.4 \times \text{UN}$)
Input voltage range 33.6 V DC ... 60 V DC
Switching threshold "0" signal in reference to UN < 0.3
Switching threshold "1" signal in reference to UN > 0.6
Typical input current at UN 5.5 mA
Typical response time 40 μs
Typical turn-off time 200 μs
Operating voltage display Yellow LED
Type of protection Reverse polarity protection
Surge protection
Protective circuit/component Series polarity protection diode
Surge voltage protection $> 150 \text{ V}$
Transmission frequency 300 Hz
Power dissipation for nominal condition 0.26 W
Output data
Output nominal voltage 110 V DC
Output voltage range 12 V DC ... 140 V DC ($t < 1 \text{ s} = 1.40 \times \text{UN}$)
Limiting continuous current 3 A (see derating curve)
Surge voltage protection $> 150 \text{ V}$
Voltage drop at max. limiting continuous current $< 150 \text{ mV}$
Output circuit 2-wire, floating
Type of protectio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-OPT-48DC/110DC/3RW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.