

INDUSTRIAL COMPONENT DATA

DF-PTMC-NS 3270403 PHOENIX CONTACT Adapter

Brand: PHOENIX CONTACT | Manufacturer Part Number: DF-PTMC-NS



Manufacturer	PHOENIX CONTACT
MPN / Reference	DF-PTMC-NS
Catalog number	3270403
Category	DIN-rail adapter
Minimum order	10 Pcs
Document ID	EO-177BB62280
Generated	2026-08-03

Product Overview

Adapter

Adapter, for rail mounting, length: 64 mm, width: 22 mm, colour: grey

Adapter, for mounting on a DIN rail, width: 22 mm, height: 64 mm, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Technical dataProduct propertiesProduct type Mounting material

Data management status

Article revision 00

DimensionsWidth 22 mm

Height 64 mm

Depth on NS 35/7,5 21.5 mm

Depth on NS 35/15 29 mm

Material specificationsColor gray (RAL 7042)

Material PA

Static insulating material application in cold -60 °C

Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C

Relative insulation material temperature index (Elec., UL 746 B) 130 °C

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354) 27,5 MJ/kg
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Environmental and real-life conditions Ambient conditions
Ambient temperature (operation) -60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly) -5 °C ... 70 °C
Ambient temperature (actuation) -5 °C ... 70 °C
Permissible humidity (storage/transport) 30 % ... 70 %
ETIM for 3270403 Low-voltage industrial controls and switchgear (EC001024)
Feature Name
Feature Value
Material (EF002169)
Plastic

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DF-PTMC-NS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.