

INDUSTRIAL COMPONENT DATA

FLKM-PA-D37/HW/C300 2322029 PHOENIX CONTACT Front adapters

Brand: PHOENIX CONTACT | Manufacturer Part Number: FLKM-PA-D37/HW/C300



Manufacturer	PHOENIX CONTACT
MPN / Reference	FLKM-PA-D37/HW/C300
Catalog number	2322029
Category	Accessories/spare parts for controls
Minimum order	1 Pcs
Document ID	EO-A8E8DD32E1
Generated	2026-08-01

Product Overview

Front adapters

VARIOFACE Front Adapter, for Honeywell C300, C I/O Series, 1 x 16 Channel Max Connection (37-Pin D-SUB Plug-in Connector)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data

Orderkey 2322029

Packing unit 1 pc

Catalog page Page 220 (IF-2011)

GTIN 4046356448253

Weight per Piece (excluding packing) 102.900 g

Custom tariff number 85366990

Country of origin DE (Germany)

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

General

Max. permissible operating voltage 25 V AC

50 V DC

Max. permissible current 1 A (per path)

4 A (per connection, supply via separate power supply)

Mounting position any

Degree of protection IP00

Connection data 1

Connection name Field level

Connection method D-SUB pin strip

Number of connections 1

Number of positions 37

Connection data 2

Connection name Supply

Connection method Spring-cage connection

Conductor cross section solid 0.2 mm² ... 4 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 12

Supported controller

Controller HONEYWELL Experion PKS C300/C-Series

- suitable I/O card TDIL01 (non-redundant)

TDOB01 (non-redundant)

Standards and Regulations

Standards/regulations IEC 60664

DIN EN 50178

Rated insulation voltage 63 V

Rated surge voltage 0.6 kV

Insulation Functional insulation

Degree of pollution 2

Overvoltage category II

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 5.027249290eCl@ss 5.127250300eCl@ss 6.027249200eCl@ss 7.0272...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FLKM-PA-D37/HW/C300 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.