

INDUSTRIAL COMPONENT DATA

AI 1 -12 RD -1000 1200311 PHOENIX CONTACT Ferrule

Brand: PHOENIX CONTACT | Manufacturer Part Number: AI 1-12 RD-1000



Manufacturer	PHOENIX CONTACT
MPN / Reference	AI 1-12 RD-1000
Catalog number	1200311
Category	Cable end sleeve
Minimum order	1000 Pcs
Document ID	EO-12470627E3
Generated	2026-08-05

Product Overview

Ferrule
Toe cap, cuff length: 12 mm, length: 18 mm, colour: red
Ferrule, sleeve length: 18 mm, color: red

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Ferrules
--------------	----------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Cable end sleeve
Conductor category stranded conductors, class 2, 5, 6 / B, C, K, M
Data management status
Article revision 02
Connection dataConductor connection
Conductor cross section flexible max. 1 mm²
Stripping length 15 mm
DimensionsDimensional drawing
Sleeve length 18 mm
Length contact range 12 mm
Maximum stripping length 15 mm
Ferrule diameter 1.5 mm
Sleeve wall thickness 0.15 mm
Insulating collar thickness 0.3 mm

Material specificationsColor red (RAL 3001)

Material CU-DHP

Flammability rating according to UL 94 HB

Coating tin-plated (galvanic)

Surface characteristics Tin-plated

Components free from silicone and halogen

Mechanical propertiesTechnical data

Sleeve length 18 mm

Environmental and real-life conditionsAmbient conditions

Permanent temperature 105 °C (-40 °C no load / 0 °C dynamic load)

Short-term temperature 120 °C

Standards and regulationsDesign according to standard DIN 46228-4, UL 486F-E, NFC 63-023

ETIM for 1200311 Cable terminations and insulation products (EC000005)

Feature Name

Feature Value

Construction type (EF000767)

Standard

Nominal cross section (EF001335)

1 mm²

Sleeve length (EF000014)

18 mm

Insulated (EF000019)

Yes

Material insulation (EF008118)

Other

Halogen free (EF000025)

Yes

Colour (EF000007)

Red

Surface protection (EF000139)

Other

For cables resistant to short circuit (EF001713)

No

With identification flag (EF007954)

No

AWG size (EF011789)

18

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AI 1-12 RD-1000 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.