

INDUSTRIAL COMPONENT DATA

AI-TWIN 2X16 -16 WH 1213207 PHOENIX CONTACT Ferrule

Brand: PHOENIX CONTACT | Manufacturer Part Number: AI-TWIN 2X16-16 WH



Manufacturer	PHOENIX CONTACT
MPN / Reference	AI-TWIN 2X16-16 WH
Catalog number	1213207
Category	Cable end sleeve
Minimum order	50 Pcs
Document ID	EO-7CD084E66B
Generated	2026-08-06

Product Overview

Ferrule
Toe cap, cuff length: 16 mm, length: 31 mm, color: white
Ferrule, sleeve length: 30 mm, color: white

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Ferrules
--------------	----------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Cable end sleeve
Conductor category stranded conductors, class 2, 5, 6 / B, C, K, M
Data management status
Article revision 03
Connection dataConductor connection
Conductor cross section flexible max. 16 mm²
Conductor cross section AWG max. 6
Stripping length 21 mm
DimensionsDimensional drawing
Sleeve length 30 mm
Length contact range 16 mm
Maximum stripping length 21 mm
Ferrule diameter 8.5 mm
Sleeve wall thickness 0.2 mm

Insulating collar thickness 0.5 mm
Inner dimensions of the insulating collar 8.8 mm
Material specifications Color white (RAL 9010)
Material CU-DHP
Flammability rating according to UL 94 HB
Coating tin-plated (galvanic)
Surface characteristics Tin-plated
Components free from silicone and halogen
Mechanical properties Technical data
Sleeve length 30 mm
Environmental and real-life conditions Ambient conditions
Permanent temperature 105 °C (-40 °C no load / 0 °C dynamic load)
Short-term temperature 120 °C
Standards and regulations Design according to standard DIN 46228-4

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AI-TWIN 2X16-16 WH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.