

INDUSTRIAL COMPONENT DATA

IB IL AI 4/EF-PAC 2878447 PHOENIX CONTACT Inline terminal

Brand: PHOENIX CONTACT | Manufacturer Part Number: IB IL AI 4/EF-PAC



Manufacturer	PHOENIX CONTACT
MPN / Reference	IB IL AI 4/EF-PAC
Catalog number	2878447
Category	Fieldbus, decentr. periphery - analogue I/O module
Minimum order	1 Pcs
Document ID	EO-341ECECA47
Generated	2026-07-31

Product Overview

Inline terminal

Inline, Analog Input Module, Analog Inputs: 4, 0 V ... 5 V, -5 V ... 5 V, 0 V ... 10 V, -10 V ... 10 V, 0 mA... 20 mA, 4 mA... 20 mA, -20 mA... 20 mA, connection technology: 2, 3, 4 conductors, transmission rate on the local bus: 500 kBit/s, protection rating: IP20, including inline connectors and marking fields

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > I/O

Additional Product Information

Key Commercial Data

Orderkey 2878447

Packing unit 1 pc

Catalog page Page 160 (C-6-2017)

GTIN 4017918996376

Weight per Piece (excluding packing) 210.000 g

Custom tariff number 85389091

Country of origin DE (Germany)

Dimensions

Dimensional drawing

Width 48.8 mm

Height 135 mm

Depth 71.5 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 55 °C

Ambient temperature (storage/transport) -25 °C ... 85 °C

Permissible humidity (operation) 10 % ... 95 % (according to DIN EN 61131-2)

Permissible humidity (storage/transport) 10 % ... 95 % (according to DIN EN 61131-2)

Air pressure (operation) 70 kPa ... 106 kPa (up to 3000 m above sea level)

Air pressure (storage/transport) 70 kPa ... 106 kPa (up to 3000 m above sea level)

Degree of protection IP20

General

Mounting type DIN rail

Net weight 210 g

Note on weight specifications with connectors

Operating mode Process data mode with 5 words/1 word PCP

Interfaces

Designation Inline local bus

Connection method Inline data jumper

Transmission speed 500 kbps

Transmission physics Copper

Inline potentials

Designation Communications power (UL)

Supply voltage 7.5 V DC (via voltage jumper)

Current consumption typ. 85 mA

max. 100 mA

Designation Supply of analog modules (UANA)

Supply voltage 24 V DC

Supply voltage range 19.2 V DC ... 30 V DC (including all tolerances, including ripple)

Current consumption typ. 13 mA

max. 20 mA

Designation Main circuit supply (UM)

Supply voltage 24 V DC (via voltage jumper)

Supply voltage range 19.2 V DC

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IB IL AI 4/EF-PAC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.