

INDUSTRIAL COMPONENT DATA

IB IL AI 4/I-PAC 2700458 PHOENIX CONTACT Inline terminal

Brand: PHOENIX CONTACT | Manufacturer Part Number: IB IL AI 4/I-PAC



Manufacturer	PHOENIX CONTACT
MPN / Reference	IB IL AI 4/I-PAC
Catalog number	2700458
Category	Fieldbus, decentr. periphery - analogue I/O module
Minimum order	1 Pcs
Document ID	EO-A1374D5112
Generated	2026-08-02

Product Overview

Inline terminal

Inline, Analog Input Module, Analog Inputs: 4, 0 mA ... 20 mA, 4 mA... 20 mA, connection technology: 2 conductors, transmission rate on local bus: 500 kBit/s, protection rating: IP20, including inline connector and marking surface

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > I/O
--------------	-----------------------

Additional Product Information

Key Commercial Data

Orderkey 2700458

Packing unit 1 pc

Catalog page Page 159 (C-6-2017)

GTIN 4046356566544

Weight per Piece (excluding packing) 66.000 g

Custom tariff number 85389091

Country of origin DE (Germany)

Note

Utilization restriction 1

Dimensions

Dimensional drawing

Width 12.2 mm

Height 119.8 mm

Depth 71.5 mm

Note on dimensions Housing dimensions

Ambient conditions

Ambient temperature (operation) -25 °C ... 55 °C

Ambient temperature (storage/transport) -25 °C ... 85 °C

Permissible humidity (operation) 10 % ... 95 % (according to DIN EN 61131-2)

Permissible humidity (storage/transport) 10 % ... 95 % (according to DIN EN 61131-2)

Air pressure (operation) 70 kPa ... 106 kPa (up to 3000 m above sea level)

Air pressure (storage/transport) 70 kPa ... 106 kPa (up to 3000 m above sea level)

Degree of protection IP20

General

Mounting type DIN rail

Net weight 66 g

Note on weight specifications with connector

Diagnostics messages Failure of the internal I/O supply I/O error message sent to the bus coupler

I/O supply failure Message in the diagnostic code (in the IB IL format)

Overrange or underrange Message in the diagnostic code (in the IB IL format)

Configuration invalid Message in the diagnostic code (in the IB IL format)

Interfaces

Designation Inline local bus

No. of channels 2

Connection method Inline data jumper

Transmission speed 500 kbps

Transmission physics Copper

Inline potentials

Designation Communications power (UL)

Supply voltage 7.5 V DC (via voltage jumper)

Curr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IB IL AI 4/I-PAC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.