

INDUSTRIAL COMPONENT DATA

AP-BTO 1,25 3281125 PHOENIX CONTACT Cover profile

Brand: PHOENIX CONTACT | Manufacturer Part Number: AP-BTO 1,25



Manufacturer	PHOENIX CONTACT
MPN / Reference	AP-BTO 1,25
Catalog number	3281125
Category	Accessories/spare parts for terminals
Minimum order	10 Pcs
Document ID	EO-D7C2DC0E14
Generated	2026-08-05

Product Overview

Cover profile

Cover profile, length: 46 mm, width: 1000 mm, height: 9.8 mm, colour: transparent

Cover profile, width: 1000 mm, height: 9.8 mm, color: transparent

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Cover profile

Insulation characteristics

Overvoltage category III

DimensionsWidth 1 m

Height 9.8 mm

Material specificationsColor transparent

Material PC

Flammability rating according to UL 94 V0

Insulating material group IIIa

Environmental and real-life conditionsAmbient conditions

Ambient temperature (operation) -60 °C ... 85 °C

Ambient temperature (storage/transport) -25 °C ... 55 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)

Ambient temperature (assembly) -5 °C ... 70 °C

Ambient temperature (actuation) -5 °C ... 70 °C

Permissible humidity (storage/transport) 30 % ... 70 %

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AP-BTO 1,25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.