

INDUSTRIAL COMPONENT DATA

APH-RSCWE 6-3 CARRIER 3069058 PHOENIX CONTACT

Cover profile carrier

Brand: PHOENIX CONTACT | Manufacturer Part Number: APH-RSCWE 6-3 CARRIER



Manufacturer	PHOENIX CONTACT
MPN / Reference	APH-RSCWE 6-3 CARRIER
Catalog number	3069058
Category	Mounting accessories (switchgear cabinet)
Minimum order	10 Pcs
Document ID	EO-D60354FC37
Generated	2026-08-05

Product Overview

Cover profile carrier

Support for cover profile, to accommodate the cover profile, length: 81 mm, width: 8.15 mm, height: 73.1 mm, number of poles: 1, color: gray, mounting class: Fit

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 3069058

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 618 (C-1-2017)

GTIN 4055626157566

Weight per Piece (excluding packing) 12.370 g

Custom tariff number 85389099

Country of origin PL (Poland)

General

Number of positions 1

Color gray

Material PA

Flammability rating according to UL 94 V0

Overvoltage category III

Insulating material group I

Relative insulation material temperature index (Elec., UL 746 B) 130 °C

Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C

Static insulating material application in cold -60 °C

Behavior in fire for rail vehicles (DIN 5510-2) Test passed

Flame test method (DIN EN 60695-11-10) V0

Oxygen index (DIN EN ISO 4589-2) >32 %

NF F16-101, NF F10-102 Class I 2

NF F16-101, NF F10-102 Class F 2

Surface flammability NFPA 130 (ASTM E 162) passed

Specific optical density of smoke NFPA 130 (ASTM E 662) passed

Smoke gas toxicity NFPA 130 (SMP 800C) passed

Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3

Dimensions

Width 8.15 mm

Length 81 mm

Height 73.1 mm

Mounting

Mounting type Snap in

Standards and Regulations

Flammability rating according to UL 94 V0

Fire protection for rail...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / APH-RSCWE 6-3 CARRIER with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.