

INDUSTRIAL COMPONENT DATA

SAC-ASI-J-Y-N-PUR-1,0-FS SCO 1407573 PHOENIX CONTACT Distributor

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-ASI-J-Y-N-PUR-1,0-FS SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-ASI-J-Y-N-PUR-1,0-FS SCO
Catalog number	1407573
Category	Sensor actuator adapter
Minimum order	1 Pcs
Document ID	EO-B521138287
Generated	2026-08-05

Product Overview

Distributor

Actuator and sensor interface splitter in high degree of protection, for branching from a flat cable to a 1.0 m PUR round cable with straight female M12 SPEEDCON

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1407573

Packing unit 1 pc

Catalog page Page 439 (C-2-2017)

GTIN 4046356779937

Weight per Piece (excluding packing) 78.000 g

Custom tariff number 85444290

Country of origin VN (Vietnam)

Dimensions

Length of cable 1 m

Ambient conditions

Degree of protection IP65

IP67

Ambient temperature (operation) -25 °C ... 75 °C
-25 °C ... 80 °C (cable, flexible installation)
-40 °C ... 80 °C (cable, fixed installation)
Ambient temperature (storage/transport) -25 °C ... 85 °C
General data
Rated current at 40°C 4 A
Rated voltage ≤ 32 V DC
Number of positions 2
Standards/regulations M12 connector IEC 61076-2-101
Overvoltage category II
Degree of pollution 3
Connection method AS-i penetration technique
Characteristics head 1
Head type Load center lateral AS-i Screw locking
No. of positions (pin connector pattern) 2
Material (component) CuSn (Contact)
Ni/Au (Contact surface)
PBT (Contact carriers)
PBT (Housing)
Stainless steel (Screw connection)
Torque 1.65 Nm (Locking screw)
Characteristics head 2
Head type Socket straight M12 SPEEDCON
No. of positions (pin connector pattern) 2 (5)
Color black
Material (component) CuSn (Contact)
Ni/Au (Contact surface)
TPU GF (Contact carriers)
TPU (Grip)
Zinc die-cast, nickel-plated (Screw connection)
Insertion/withdrawal cycles ≥ 100
Torque 0.4 Nm
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-101
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
UL AWM style 205...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-ASI-J-Y-N-PUR-1,0-FS SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.