

INDUSTRIAL COMPONENT DATA

SAC-ASI-J-Y-Y-N 1405622 PHOENIX CONTACT Distributor

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-ASI-J-Y-Y-N



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-ASI-J-Y-Y-N
Catalog number	1405622
Category	Sensor actuator adapter
Minimum order	1 Pcs
Document ID	EO-B4BC00D815
Generated	2026-08-05

Product Overview

Distributor

Highly protected H AS-Interface distributor connected in parallel for the distribution of flat cables AS Interface

AS-Interface H-distributor with a high degree of protection, parallel wired, for the distribution of AS-Interface flat-ribbon conductors

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Technical dataProduct propertiesProduct type Network distributor box

Number of positions 4

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical propertiesNominal voltage UN <= 32 V DC

Nominal current IN 8 A

Transmission medium Copper

Connection dataConnection technology

Connection method AS-i penetration technique

InterfacesBus system AS-Interface

SignalingStatus display no

Status display present No

Material specificationsMaterial Housing PBT
ConnectorConnection 1
Type Load center AS-i Screw locking
Number of positions 4
Locking type Screw locking mechanism
Material CuSn (Contact)
Ni/Au (Contact surface)
PBT (Contact carriers)
PBT (Housing)
Stainless steel (Screw connection)
Tightening torque 1.65 Nm (Locking screw)
Environmental and real-life conditionsAmbient conditions
Degree of protection IP65
IP67
IP69K
Ambient temperature (operation) -25 °C ... 75 °C
Ambient temperature (storage/transport) -25 °C ... 85 °C
ETIM for 1405622 Sensors (EC002925)
Feature Name
Feature Value
Model (EF000010)
Single
Screened (EF000881)
No
Housing material (EF001596)
Other
Ambient temperature (EF002386)
75 °C
Operating temperature (EF002393)
-25 °C
Degree of protection (IP), mounted (EF007466)
IP65
Material thread ring (EF012304)
Stainless steel
Rated voltage (EF000228)
32 V
Rated current I_n (EF008250)
8 A
Pollution degree (EF006786)
1
Material of contact surface (EF004020)
Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-ASI-J-Y-Y-N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.