

INDUSTRIAL COMPONENT DATA

CRIMPSET 6 1202072 PHOENIX CONTACT Tool set

Brand: PHOENIX CONTACT | Manufacturer Part Number: CRIMPSET 6



Manufacturer	PHOENIX CONTACT
MPN / Reference	CRIMPSET 6
Catalog number	1202072
Category	Assortment box for installation- and connection material
Minimum order	1 Pcs
Document ID	EO-4F6DAA4176
Generated	2026-08-03

Product Overview

Tool set

Assortment box, made of metal, equipped with ferrules according to DIN 46228-4: 1990-09, each with 500 pcs. AI 0.25-6 YE, AI 0.34-6 TQ, AI 0.5-8 WH, AI 0.75-8 GY, AI 1-8 RD, AI 1.5-8 BK, 300 pcs. AI 2.5-8 BU, 200 pcs. AI 4-10 GY, 100 pcs. AI 6-12 YE, CRIMPFOX DUO 10, QUICK WIREFOX 6

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > TOOL fox
--------------	----------------------------

Additional Product Information

Key Commercial Data

Orderkey 1202072

Packing unit 1 pc

Catalog page Page 469 (C-3-2017)

GTIN 4017918017699

Weight per Piece (excluding packing) 2,826.200 g

Custom tariff number 82060000

Country of origin SE (Sweden)

Dimensions

Length (b) 206 mm

Width (a) 357 mm

Height (c) 48 mm

General

Base element material Metal

Environmental Product Compliance

California Proposition 65 Further information on California's prop. 65 is available under "Downloads" in the manufacturer's declaration

Articles in set

Ferrule, sleeve length: 6 mm, length: 10.5 mm, color: yellow

Ferrule, sleeve length: 6 mm, length: 10.5 mm, color: turquoise

Ferrule, sleeve length: 8 mm, length: 14 mm, color: white

Ferrule, sleeve length: 8 mm, length: 14 mm, color: gray

Ferrule, sleeve length: 8 mm, length: 14 mm, color: red

Ferrule, sleeve length: 8 mm, length: 14 mm, color: black

Ferrule, sleeve length: 8 mm, length: 14 mm, color: blue

Ferrule, sleeve length: 10 mm, length: 17 mm, color: gray

Ferrule, sleeve length: 12 mm, length: 20 mm, color: yellow

Stripping tool for cables with PVC insulation, stripping range: 0.08 to 6 mm², wire cutting up to 6 mm² flexible or 4 mm² rigid

Crimping pliers, for ferrules without insulating collar according to DIN 46228 Part 1 and ferrules with insulating collar according to DIN 46228 Part 4, 0.25 mm² ... 6 mm², lateral entry, trapezoidal crimp

Classifications

eCl@ss 4.021040301eCl@ss 4.121040301eCl@ss 5.021043090eCl@ss 5.127400200eCl@ss 6.027400200eCl@ss 7.027400218eCl@ss 8.027...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CRIMPSET 6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.