

INDUSTRIAL COMPONENT DATA

CN-LAMBDA/4-2.25-BB 2801057 PHOENIX CONTACT

Attachment plug with Lambda/4 technology as surge protection for..

Brand: PHOENIX CONTACT | Manufacturer Part Number: CN-LAMBDA/4-2.25-BB



Manufacturer	PHOENIX CONTACT
MPN / Reference	CN-LAMBDA/4-2.25-BB
Catalog number	2801057
Category	Surge protection device for data networks/MCR-technology
Minimum order	1 Pcs
Document ID	EO-E73011C5D9
Generated	2026-07-31

Product Overview

Attachment plug with Lambda/4 technology as surge protection for coaxial signal interfaces. Connection: N connectors socket-socket

Adapter with Lambda/4 technology as surge protection for coaxial signal interfaces. Connection: N Female-Female Connectors

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)
--------------	---------------------------------

Additional Product Information

Dimensions

Height 78.7 mm

Width 25 mm

Depth 77.5 mm

Length 77.5 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 85 °C

Degree of protection IP68

General

Housing material HPb59-1

Color nickel
Standards for clearances and creepage distances IEC 60664-1
Mounting type Connection-specific intermediate plugging
Type Attachment plug
Number of positions 1
Direction of action Line-Shield/Earth Ground
Protective circuit
IEC test classification C2
C3
D1
Nominal current I_N 5 A (25 °C)
Nominal discharge current $I_n(8/20)$ μ s 50 kA
Nominal discharge current $I_n(8/20)$ μ s (Core-Earth) 50 kA
Nominal discharge current $I_n(8/20)$ μ s (Core-Shield) 50 kA
Total surge current (8/20) μ s 60 kA
Total surge current (10/350) μ s 20 kA
Max. discharge current $I_{max}(8/20)$ μ s 60 kA
Max. discharge current $I_{max}(8/20)$ μ s maximum (Core-Earth) 60 kA
Max. discharge current $I_{max}(8/20)$ μ s maximum (Core-Shield) 60 kA
Impulse discharge current (10/350) μ s, peak value I_{imp} 20 kA
Output voltage limitation at 1 kV/ μ s (Core-Earth) spike ≤ 1 V
Output voltage limitation at 1 kV/ μ s (Core-Shield) spike ≤ 1 V
Voltage protection level $U_p(\text{core-ground}) \leq 25$ V (C2 - 10 kV / 5 kA)
 ≤ 5 V (C1 - 1 kV/500 A)
 ≤ 18 V (6 kV/3 kA)
Voltage protection level $U_p(\text{core-shield}) \leq 5$ V (C1 - 1 kV/500 A)
 ≤ 25 V (C2 - 10 kV / 5 kA)
 ≤ 18 V (6 kV/3 kA)
Input attenuation aE, asym. typ. 0.1 dB
Frequency range 0.8 GHz ... 2.25 GHz
Standing wave ratio SWR in a 50 Ω system typ. 1.2
max. 1.25
Permissible HF power P_{maxat} VSWR = xx (50 ohm system) $\leq$

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CN-LAMBDA/4-2.25-BB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.