

INDUSTRIAL COMPONENT DATA

CN-LAMBDA/4-5.9-BB 2838490 PHOENIX CONTACT Surge protection device

Brand: PHOENIX CONTACT | Manufacturer Part Number: CN-LAMBDA/4-5.9-BB



Manufacturer	PHOENIX CONTACT
MPN / Reference	CN-LAMBDA/4-5.9-BB
Catalog number	2838490
Category	Surge protection device for data networks/MCR-technology
Minimum order	1 Pcs
Document ID	EO-DFBC9536A5
Generated	2026-07-29

Product Overview

Surge protection device

Adapter with Lambda/4 technology as surge protection for coaxial signal interfaces. Connection: N Female-Female Connectors

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Trabtech (TT)

Additional Product Information

Key Commercial Data

Orderkey 2838490

Packing unit 1 pc

Catalog page Page 179 (C-4-2017)

GTIN 4046356285629

Weight per Piece (excluding packing) 140.190 g

Custom tariff number 85363010

Country of origin US (United States)

Dimensions

Height 38 mm

Width 26.1 mm

Depth 60 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 90 °C

Degree of protection IP68

General

Housing material Brass (CuZn)

Color nickel

Mounting type Connection-specific intermediate plugging

Type Attachment plug

Number of positions 1

Direction of action Line-Shield/Earth Ground

Protective circuit

IEC test classification C2

C3

D1

VDE requirement class C2

C3

D1

Rated current 5 A (25 °C)

Nominal discharge current $I_n(8/20) \mu s$ (line-earth) 50 kA

Nominal discharge current $I_n(8/20) \mu s$ (line-shield) 50 kA

Pulse discharge current $I_{imp}(10/350) \mu s$ (line-earth) ≤ 20 kA

Total discharge current $I_{total}(8/20) \mu s$ 60 kA

Total discharge current $I_{total}(10/350) \mu s$ 20 kA

Max. discharge current $I_{max}(8/20) \mu s$ maximum (line-earth) 60 kA

Max. discharge current $I_{max}(8/20) \mu s$ maximum (line-shield) 60 kA

Output voltage limitation at 1 kV/ μs (line-earth) spike ≤ 11 V (6 kV / 3 kA)

Output voltage limitation at 1 kV/ μs (line-shield) spike ≤ 11 V (6 kV / 3 kA)

Output voltage limitation at 1 kV/ μs (line-earth) static ≤ 11 V (6 kV / 3 kA)

Output voltage limitation at 1 kV/ μs (line-shield) static ≤ 11 V (6 kV / 3 kA)

Voltage protection level U_p (line-earth) ≤ 11 V (6 kV / 3 kA)

Voltage protection level U_p (line-shield) ≤ 11 V (6 kV / 3....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CN-LAMBDA/4-5.9-BB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.