

INDUSTRIAL COMPONENT DATA

CN-UB-280DC-3-BB 2801050 PHOENIX CONTACT Surge protection device

Brand: PHOENIX CONTACT | Manufacturer Part Number: CN-UB-280DC-3-BB



Manufacturer	PHOENIX CONTACT
MPN / Reference	CN-UB-280DC-3-BB
Catalog number	2801050
Category	Surge protection device for data networks/MCR-technology
Minimum order	1 Pcs
Document ID	EO-B1A6FD7801
Generated	2026-07-29

Product Overview

Surge protection device

Replaceable surge protection adapter for coaxial signal interfaces. Connection: N Female Connector

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Trabtech (TT)

Additional Product Information

Key Commercial Data

Orderkey 2801050

Packing unit 1 pc

Catalog page Page 176 (C-4-2017)

GTIN 4046356675727

Weight per Piece (excluding packing) 145.000 g

Custom tariff number 85363010

Country of origin CN (China)

Dimensions

Height 33.5 mm

Width 31 mm

Length 57.8 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 80 °C

Altitude 2000 m
Degree of protection IP55
IP55
General
Housing material HPb59-1
Color nickel
Standards for clearances and creepage distances IEC 60664-1
Mounting type Connection-specific intermediate plugging
Type Attachment plug
Number of positions 1
Direction of action Line-Shield/Earth Ground
Protective circuit
IEC test classification C2
C3
D1
Maximum continuous voltage UC 280 V DC
Maximum continuous voltage UC(line-earth) 280 V DC
Rated current 5 A (25 °C)
Operating effective current $I_{Cat UC} \leq 1 \mu A$
Nominal discharge current $I_n(8/20) \mu s$ 20 kA
Nominal discharge current $I_n(8/20) \mu s$ (line-earth) 20 kA
Nominal discharge current $I_n(8/20) \mu s$ (line-shield) 20 kA
Total surge current (10/350) μs 2.5 kA
Total discharge current $I_{total}(8/20) \mu s$ 20 kA
Max. discharge current $I_{max}(8/20) \mu s$ 20 kA
Max. discharge current $I_{max}(8/20) \mu s$ maximum (line-earth) 20 kA
Max. discharge current $I_{max}(8/20) \mu s$ maximum (line-shield) 20 kA
Nominal pulse current $I_{an} (10/1000) \mu s$ (Core-Shield) 100 A
Impulse discharge current (10/350) μs , peak value I_{imp} 2.5 kA
Output voltage limitation at 1 kV/ μs (line-earth) spike $\leq 900 V$
Output voltage limitation at 1 kV/ μs (line-shield) spike....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CN-UB-280DC-3-BB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.