

INDUSTRIAL COMPONENT DATA

C-UB/E 2763701 PHOENIX CONTACT Surge protection device

Brand: PHOENIX CONTACT | Manufacturer Part Number: C-UB/E



Manufacturer	PHOENIX CONTACT
MPN / Reference	C-UB/E
Catalog number	2763701
Category	Surge protection device for data networks/MCR-technology
Minimum order	1 Pcs
Document ID	EO-D8E837FA11
Generated	2026-07-29

Product Overview

Surge protection device

Adapter with surge protection for coaxial signal interfaces with display without earth potential. Connection: Female-male BNC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)
--------------	---------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2763701

Packing unit 10 pc

Catalog page Page 177 (C-4-2017)

GTIN 4017918065638

Weight per Piece (excluding packing) 102.400 g

Custom tariff number 85363010

Country of origin DE (Germany)

Dimensions

Height 25.4 mm

Width 25.4 mm

Depth 80 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 80 °C

Altitude ≤ 2000 m (amsl (above mean sea level))

Degree of protection IP20

General

Housing material Aluminum

Mounting type Connection-specific intermediate plugging

Type Attachment plug

Direction of action Line-Shield/Earth Ground

Additional descriptions

Note To meet the discharge conditions for DC voltages, please note the following information: "The surge protective device should be used together with a transmitter unit, which shuts down in the event of a short-circuit."

Protective circuit

IEC test classification C2

C3

D1

Maximum continuous voltage UC 180 V DC

130 V AC

Rated current 3.5 A (25 °C)

Operating effective current I_{Cat} UC $\leq 1 \mu A$

Residual current IPE $\leq 2 \mu A$

Nominal discharge current $I_n(8/20) \mu s$ (line-earth) 5 kA

Nominal discharge current $I_n(8/20) \mu s$ (line-shield) 5 kA

Nominal discharge current $I_n(8/20) \mu s$ (shield-earth) 5 kA

Pulse discharge current $I_{imp}(10/350) \mu s$ (line-earth) 2.5 kA

Pulse discharge current $I_{imp}(10/350) \mu s$ (line-shield) 2.5 kA

Total discharge current $I_{total}(8/20) \mu s$ 10 kA

Output voltage limitation at 1 kV/ μs (line-earth) spike ≤ 470 V

Output voltage limitation at 1 kV/ μs (line-shield) spike ≤ 590 V

Output voltage limit...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / C-UB/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.