

INDUSTRIAL COMPONENT DATA

AXC F XT KIT 1383116 PHOENIX CONTACT Stackable on the left, expansion module equipped with mini PCIe slot fo..

Brand: PHOENIX CONTACT | Manufacturer Part Number: AXC F XT KIT



Manufacturer	PHOENIX CONTACT
MPN / Reference	AXC F XT KIT
Catalog number	1383116
Category	Fieldbus, decentr. periphery - communication module
Minimum order	1 Pcs
Document ID	EO-C483188865
Generated	2026-08-05

Product Overview

Stackable on the left, expansion module equipped with mini PCIe slot for connection to a PLCnext controller type AXC F 2152 or AXC F 3152

Side-by-side expansion module on the left, equipped with Mini PCIe slot for connection to a PLCnext controller of the type AXC F 2152 or AXC F 3152

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Control Systems (CST)

Additional Product Information

Technical dataDimensionsDimensioned Drawing

width 45 mm

height 126.93 mm

Depth 75 mm

Size Note The depth applies to the use of a TH 35-7.5 support rail (according to EN 60715).

Article featurestype modularity

Product Type I/O Components

Product Family PLCnext Control Extension

Electrical characteristicsPotentials: U logic voltage supplyL

Power supply voltage 24 V DC

Supply voltage range 19.2 V DC ... 30 V DC (including all tolerances, including ripple)

Current consumption tip. 15.5 mA (without Mini PCIe module)

Protection Circuit Prot. reverse polarity; Diode against inv. polarity
protection from transient phenomena; Diode Suppressor
Potential
Power supply voltage 24 V DC
Supply voltage range 19.2 V DC ... 30 V DC (including all tolerances, including ripple)
Current consumption without Mini PCIe module
without Mini PCIe module
Environmental and electrical life conditionsEnvironmental conditions
Ambient temperature (operation) -25 °C ... 60 °C (up to 2000 m a.s.l., without Mini PCIe module)
Degree of protection Ip20
Air pressure (operation) 70 kPa ... 106 kPa (up to 3000 m a.s.l., without Mini PCIe module)
Permissible humidity (operation) 5 % ... 95 % (in accordance with DIN EN 61131-2, without Mini PCIe module)
Regulations and requirementsSecurity class III (IEC 61140, EN 61140, VDE 0140-1)
MontageMounting type Rail Mounting
ETIM for 1383116 PLC's (EC001604)
Feature Name
Feature Value
Supply voltage DC (EF007534)
19.2 V
Voltage type (supply voltage) (EF002991)
DC
Radio stand...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AXC F XT KIT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.