

INDUSTRIAL COMPONENT DATA

AXL E PN IOL8 DI4 M12 6M 2701519 PHOENIX CONTACT

Distributed I/O device

Brand: PHOENIX CONTACT | Manufacturer Part Number: AXL E PN IOL8 DI4 M12 6M



Manufacturer	PHOENIX CONTACT
MPN / Reference	AXL E PN IOL8 DI4 M12 6M
Catalog number	2701519
Category	Fieldbus, decentr. periphery - digital I/O module
Minimum order	1 Pcs
Document ID	EO-637A6BF1C7
Generated	2026-08-05

Product Overview

Distributed I/O device

AxiolineE-PROFINET device in metal housing with 8 IO-Link ports and 4 digital inputs, 24VDC, M12 quick connect technology

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > I/O

Additional Product Information

Key Commercial Data

Orderkey 2701519

Packing unit 1 pc

Catalog page Page 199 (C-6-2017)

GTIN 4046356763691

Weight per Piece (excluding packing) 708.700 g

Custom tariff number 85176200

Country of origin DE (Germany)

Note

Utilization restriction 1

Dimensions

Dimensional drawing

Width 60 mm

Height 185 mm

Depth 38 mm

Note on dimensions The height is 194.5 mm including the mounting plate. With fixing clips pulled out, the height is 212 mm. The depth is 38 mm including the mounting plate (30.5 mm without the mounting plate).

Drill hole spacing 198.5 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 60 °C

Ambient temperature (storage/transport) -25 °C ... 85 °C

Permissible humidity (operation) 5 % ... 95 %

Permissible humidity (storage/transport) 5 % ... 95 %

Air pressure (operation) 70 kPa ... 106 kPa (up to 3000 m above sea level)

Air pressure (storage/transport) 70 kPa ... 106 kPa (up to 3000 m above sea level)

Degree of protection IP65/IP67

General

Housing material Zinc die-cast

Mounting type Wall mounting or DIN rail mounting; both with mounting plate.

Net weight 708.7 g

Interfaces

Designation PROFINET

No. of channels 2

Connection method M12 fast connection technology

Note on the connection method D-coded

Designation connection point Copper cable

Transmission speed 100 Mbps (with auto negotiation)

Number of positions 4

System limits of the bus coupler

Designation PROFINET

Equipment type PROFINET-Device

Conformance class B

Number of supported application relation...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AXL E PN IOL8 DI4 M12 6M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.