

INDUSTRIAL COMPONENT DATA

AXL F DO4/3 AC 1F 2702068 PHOENIX CONTACT I/O module

Brand: PHOENIX CONTACT | Manufacturer Part Number: AXL F DO4/3 AC 1F



Manufacturer	PHOENIX CONTACT
MPN / Reference	AXL F DO4/3 AC 1F
Catalog number	2702068
Category	Fieldbus, decentr. periphery - digital I/O module
Minimum order	1 Pcs
Document ID	EO-DCAEDB67EF
Generated	2026-08-06

Product Overview

I/O module

AxiolineF, Digital output module, Digital outputs:4 (Triac outputs with zero voltage switch), 230 VAC, 2 A, connection technology:3 conductors, transmission speed on the local bus:100 MBit/s, protection index: IP20, including bus socket module and AxiolineF connectors

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > I/O
--------------	-----------------------

Additional Product Information

Key Commercial Data

Orderkey 2702068

Packing unit 1 pc

Catalog page Page 110 (C-6-2017)

GTIN 4046356933087

Weight per Piece (excluding packing) 239.000 g

Custom tariff number 85389091

Country of origin DE (Germany)

Dimensions

Dimensional drawing

Width 53.6 mm

Height 126.1 mm

Depth 54 mm

Note on dimensions The depth is valid when a TH 35-7,5 DIN rail is used (according to EN 60715).

Ambient conditions

Ambient temperature (operation) -25 °C ... 60 °C (max. 2 A/channel for wall mounting on horizontal DIN rail; max. 1 A/channel for any mounting position)

-25 °C ... 50 °C (max. 2 A/channel for any mounting position)

Ambient temperature (storage/transport) -40 °C ... 85 °C

Permissible humidity (operation) 5 % ... 95 % (non-condensing)

Permissible humidity (storage/transport) 5 % ... 95 % (non-condensing)

Air pressure (operation) 70 kPa ... 106 kPa (up to 3000 m above sea level)

Air pressure (storage/transport) 70 kPa ... 106 kPa (up to 3000 m above sea level)

Degree of protection IP20

Connection data

Designation Axioline F connector

Connection method Push-in connection

Note on the connection method Please observe the information provided on conductor cross sections in the "Axioline F: system and installation" user manual.

When selecting the cables, please note that in the case of a small conductor cross section and high current, the terminal point temperature may be up to 30 K above the ambient temperature.

Conductor cross section solid min. 0.5 mm²

Conductor cross section solid m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AXL F DO4/3 AC 1F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.