

INDUSTRIAL COMPONENT DATA

AXL E ETH IOL8 DI4 M12 6P 2701536 PHOENIX CONTACT

Distributed I/O device

Brand: PHOENIX CONTACT | Manufacturer Part Number: AXL E ETH IOL8 DI4 M12 6P



Manufacturer	PHOENIX CONTACT
MPN / Reference	AXL E ETH IOL8 DI4 M12 6P
Catalog number	2701536
Category	Fieldbus, decentr. periphery - digital I/O module
Minimum order	1 Pcs
Document ID	EO-F638F55F0D
Generated	2026-08-05

Product Overview

Distributed I/O device

AxiolineE-Ethernet device in plastic housing with 8 IO-Link ports and 4 digital inputs, 24V DC, M12 quick connect technology

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > I/O
--------------	-----------------------

Additional Product Information

Key Commercial Data

Orderkey 2701536

Packing unit 1 pc

Catalog page Page 197 (C-6-2017)

GTIN 4046356763844

Weight per Piece (excluding packing) 554.300 g

Custom tariff number 85176200

Country of origin DE (Germany)

Note

Utilization restriction 1

Dimensions

Dimensional drawing

Width 60 mm

Height 185 mm

Depth 30.5 mm

Note on dimensions The height is 212 mm including fixing clips.

Drill hole spacing 198.5 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 60 °C

Ambient temperature (storage/transport) -25 °C ... 85 °C

Permissible humidity (operation) 5 % ... 95 %

Permissible humidity (storage/transport) 5 % ... 95 %

Air pressure (operation) 70 kPa ... 106 kPa (up to 3000 m above sea level)

Air pressure (storage/transport) 70 kPa ... 106 kPa (up to 3000 m above sea level)

Degree of protection IP65/IP67

General

Housing material Pocan®

Mounting type Wall mounting

Net weight 554.3 g

Interfaces

Designation Ethernet

No. of channels 2

Connection method M12 fast connection technology

Note on the connection method D-coded

Designation connection point Copper cable

Transmission speed 10/100 Mbps (with auto negotiation)

Number of positions 4

System limits of the bus coupler

Designation Modbus/TCP

Equipment type Modbus slave (server)

System-specific protocols Modbus protocols Modbus/TCP

Protocols supported SNMP v1

HTTP

TFTP

FTP

BootP

DHCP

Specification Modbus application protocol V1.1b

Supply

Designation Module electronics and sensors (US)

Connection method M12 connector (T-cod...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AXL E ETH IOL8 DI4 M12 6P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.