

INDUSTRIAL COMPONENT DATA

AXL E IOL SDI8 SDO4 2A M12 L 1185380 PHOENIX CONTACT

Axioline E safety module, 4 secure digital inputs with ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: AXL E IOL SDI8 SDO4 2A M12 L



Manufacturer	PHOENIX CONTACT
MPN / Reference	AXL E IOL SDI8 SDO4 2A M12 L
Catalog number	1185380
Category	Fieldbus, decentr. periphery - digital I/O module
Minimum order	1 Pcs
Document ID	EO-9C8E844979
Generated	2026-08-02

Product Overview

Axioline E safety module, 4 secure digital inputs with 2-channel occupancy, 8 safe digital inputs with single-channel occupancy, 4 safe digital outputs with +/- switching, IO-Link interface, IP65/IP67 rating, for PROFI-safe systems

Axioline E Safety Module, 4 Secure Digital Inputs with 2 Channel Occupancy, 8 Secure Digital Inputs with One Channel Occupancy, 4 Safe Digital Outputs with +/- Switching, IO-Link Interface, IP65/IP67 Degree of Protection, for PROFI-safe Systems

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Safety
--------------	--------------------------

Additional Product Information

Technical dataDimensionsDimension Scheme

Width 59.8 mm

Height 214 mm

Depth 30 mm

Note on Measurement Indications Data incl. fixing tabs and plugs

Material DataShell material Plastic POCAN B4239 GF30 YE 1018

Input dataDigital

Denomination Entry Secure Digital Inputs

Ticket Description IEC 61131-2 Type 3

Number of Entries 4 (With 2 channel assignment)

8 (With 1 channel assignment)

Cable length max. 200 m
Connection type M12 plug-in connector (A-coded)
Connection technology 3 conductors
Input Voltage Range Signal "0" -30 V DC ... 5 V DC
Input Voltage Range Signal "1" 11 V DC ... 30.2 V DC
Nominal Input Voltage UIN 24 V DC
Nominal input current to UIN Typ. 3.7 mA (with 24 V DC)
max. 4.3 mA (with 30.2 V DC)
Inlet Filter Time 1.5 ms
3 ms (Default)
5 ms
15 ms
Protection Circuit Overload protection, short-circuit protection of sensor power
IO-Link
Number of ports 1
Connection type M12 plug-in connector, A-coded
Connection technology 3 conductors
Port Model Class A
Specification V1.1.2
Polarity reversal protection Yes
Transmission speed 230.4 kBit/s (COM3)
Cycle Time ≥ 4 ms
Updating Process Data ≥ 4 ms
Number of process data 64 Bit (Input and Output Data)
Output DataDigital
Denomination Output Secure Digital Outputs
Connection type M12 plug-in connector (A-coded)
Connection technology 2 conductors
Number of outputs 4 (with 2-channel assignment, +/- switching)
4 (with 1-channel assignment, + switching)
Protection Circuit Overload protection, outputs short-circuit protection
Output vol...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AXL E IOL SDI8 SDO4 2A M12 L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.