

INDUSTRIAL COMPONENT DATA

AXL F AI8 HART XC 1F 1052434 PHOENIX CONTACT Axioline F, Analog Input Module, Active Analog Inputs: 8 (HART)..

Brand: PHOENIX CONTACT | Manufacturer Part Number: AXL F AI8 HART XC 1F



Manufacturer	PHOENIX CONTACT
MPN / Reference	AXL F AI8 HART XC 1F
Catalog number	1052434
Category	Fieldbus, decentr. periphery - analogue I/O module
Minimum order	1 Pcs
Document ID	EO-DB4A46C12A
Generated	2026-08-03

Product Overview

Axioline F, Analog Input Module, Active Analog Inputs: 8 (HART), 4 mA ... 20 mA, connection technology: 2 conductors, transmission rate on the local bus: 100 MBit/s, Variant Extreme Conditions, HART - Functionality, HART - Functionality, protection rating: IP20, including bus socket module and Axioline F connectors

Axioline F XC, Analog Input Module, Analog Inputs: 8,4 mA ... 20 mA, connection technique: 2 conductors, transmission speed on local bus: 100 MBit/s, Extreme Conditions variant, protection index: IP20, including bus dezócalo module and Axioline F connectors

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > I/O

Additional Product Information

ETIM for 1052434 PLC's (EC001596)

Feature Name

Feature Value

Supply voltage DC (EF007534)

19.2 V

Voltage type (supply voltage) (EF002991)

DC

Input, current (EF003204)

Yes

Input, voltage (EF003205)

No
Input, resistor (EF003206)
No
Input, resistance thermometer (EF003207)
No
Input, thermocouple (EF003208)
No
Input signal, configurable (EF003209)
Yes
Resolution of the analogue inputs (EF003575)
12 Bit
Output, current (EF003212)
No
Output, voltage (EF003213)
No
Output signal configurable (EF003214)
No
Number of analogue inputs (EF001994)
8
Number of analogue outputs (EF001995)
0
Analogue inputs configurable (EF008518)
Yes
Analogue outputs configurable (EF008519)
No
Number of HW-interfaces industrial Ethernet (EF003020)
0
Number of interfaces PROFINET (EF006932)
0
Number of HW-interfaces RS-232 (EF003021)
0
Number of HW-interfaces RS-422 (EF003022)
0
Number of HW-interfaces RS-485 (EF003023)
0
Number of HW-interfaces serial TTY (EF003024)
0
Number of HW-interfaces parallel (EF003026)
0
Number of HW-interfaces wireless (EF006933)
0
Number of HW-interfaces USB (EF003025)
0
Number of HW-interfaces other (EF003027)
0
Supporting protocol for EtherCAT (EF017564)
No

Supporting protocol for TCP/IP (EF003050)

No

Supporting protocol for PROFIBUS (EF003052)

No

Supporting protocol for CAN (EF003053)

No

Supporting protocol for INTERBUS (EF003054)

No

Supporting protocol for ASI (EF003051)

No

Supporting protocol for KNX (EF003055)

No

Supporting protocol for Modbus (EF003057)

No

Supporting proto...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AXL F AI8 HART XC 1F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.