

INDUSTRIAL COMPONENT DATA

AXL F DI16 NAM XC 1F 1052427 PHOENIX CONTACT Axioline F, Digital input module, Digital inputs: 16 (NAMUR), 8..

Brand: PHOENIX CONTACT | Manufacturer Part Number: AXL F DI16 NAM XC 1F



Manufacturer	PHOENIX CONTACT
MPN / Reference	AXL F DI16 NAM XC 1F
Catalog number	1052427
Category	Fieldbus, decentr. periphery - digital I/O module
Minimum order	1 Pcs
Document ID	EO-845F788058
Generated	2026-08-06

Product Overview

Axioline F, Digital input module, Digital inputs: 16 (NAMUR), 8 V DC, connection technology: 2 conductors, Extreme Condition variant, transmission speed on local bus: 100 MBit/s, protection rating: IP20, including bus socket module and Axioline F connectors

Axioline F XC, Digital Input Module, Digital Inputs: 16 (NAMUR), 8 V DC, Connection Technique: 2 Conductors, Extreme Conditions Variant, Local Bus Transmission Rate: 100 MBit/s, Protection Index: IP20, Including Bus Socket Module and Axioline F Connectors

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > I/O

Additional Product Information

ETIM for 1052427 PLC's (EC001599)
Feature Name
Feature Value
Voltage type (supply voltage) (EF002991)
DC
Number of digital inputs (EF001992)
16
Number of digital outputs (EF001993)
0
Digital inputs configurable (EF008516)

No

Digital outputs configurable (EF008520)

No

Permitted voltage at input (EF007554)

8.2 V

Type of voltage (input voltage) (EF003033)

DC

Type of digital output (EF003601)

None

Short-circuit protection, outputs available (EF003203)

No

Number of HW-interfaces industrial Ethernet (EF003020)

0

Number of interfaces PROFINET (EF006932)

0

Number of HW-interfaces RS-232 (EF003021)

0

Number of HW-interfaces RS-422 (EF003022)

0

Number of HW-interfaces RS-485 (EF003023)

0

Number of HW-interfaces serial TTY (EF003024)

0

Number of HW-interfaces parallel (EF003026)

0

Number of HW-interfaces wireless (EF006933)

0

Number of HW-interfaces USB (EF003025)

0

Number of HW-interfaces other (EF003027)

0

With optical interface (EF003028)

No

Radio standard Bluetooth (EF007178)

No

Radio standard WLAN 802.11 (EF007179)

No

Radio standard GPRS (EF008523)

No

Radio standard GSM (EF008524)

No

Radio standard UMTS (EF008525)

No

IO link master (EF007298)

No

System accessory (EF004118)

Yes

Degree of protection (IP) (EF005474)

IP20

Type of electric connection (EF003961)

Other

Time delay at signal change (EF002382)

0 ms

Fieldbus connection over separate bus coupler possible (EF004002)

Yes

Suitable for rail mounting (EF003972)

Yes

Wall mounting/direct mounting (EF007020)

No

Front built-in possibl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AXL F DI16 NAM XC 1F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.