

INDUSTRIAL COMPONENT DATA

AXL F SGI2 1H 2702911 PHOENIX CONTACT I/O module

Brand: PHOENIX CONTACT | Manufacturer Part Number: AXL F SGI2 1H



Manufacturer	PHOENIX CONTACT
MPN / Reference	AXL F SGI2 1H
Catalog number	2702911
Category	Fieldbus, decentr. periphery - analogue I/O module
Minimum order	1 Pcs
Document ID	EO-E8787FAA7F
Generated	2026-08-03

Product Overview

I/O module

AxiolineF, Extensometer logging module, transmission rate on local bus: 100 MBit/s, protection rating: IP20, including bus socket module and AxiolineF connectors

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > I/O
--------------	-----------------------

Additional Product Information

Key Commercial Data

Orderkey 2702911

Packing unit 1 pc

GTIN 4055626459288

Weight per Piece (excluding packing) 187.700 g

Custom tariff number 85389091

Country of origin DE (Germany)

Dimensions

Dimensional drawing

Width 35 mm

Height 126.1 mm

Depth 54 mm

Note on dimensions The depth is valid when a TH 35-7,5 DIN rail is used (according to EN 60715).

Ambient conditions

Ambient temperature (operation) -25 °C ... 60 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Permissible humidity (operation) 5 % ... 95 % (non-condensing)
Permissible humidity (storage/transport) 5 % ... 95 % (non-condensing)
Air pressure (operation) 70 kPa ... 106 kPa (up to 3000 m above sea level)
Air pressure (storage/transport) 70 kPa ... 106 kPa (up to 3000 m above sea level)
Degree of protection IP20
General
Mounting type DIN rail
Net weight 187.7 g
Note on weight specifications with connectors and bus base module
Operating mode Process data mode with 6 words
Interfaces
Designation Axioline F local bus
No. of channels 2
Connection method Bus base module
Transmission speed 100 Mbps
Axioline potentials
Designation Axioline F local bus supply (UBus)
Supply voltage 5 V DC (via bus base module)
Current consumption typ. 65 mA
max. 75 mA
Power consumption typ. 325 mW
max. 375 mW
Designation Supply for analog modules (UA)
Supply voltage 24 V DC
Supply voltage range 19.2 V DC ... 30 V DC (including all tolerances, including ripple)
Current consumption typ. 25 mA (with typical load: 1 weighing cell with...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AXL F SGI2 1H with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.