

INDUSTRIAL COMPONENT DATA

AXL F UTH8 XC 1F 2702464 PHOENIX CONTACT I/O module

Brand: PHOENIX CONTACT | Manufacturer Part Number: AXL F UTH8 XC 1F



Manufacturer	PHOENIX CONTACT
MPN / Reference	AXL F UTH8 XC 1F
Catalog number	2702464
Category	Fieldbus, decentr. periphery - analogue I/O module
Minimum order	1 Pcs
Document ID	EO-B45AC78F13
Generated	2026-08-01

Product Overview

I/O module

AxiolineF, Temperature recording module, Analogue inputs: 8 (8 inputs for thermal or linear voltage elements, add. 1 input -5 V to +5 V), connection technology: 2 conductors (shielded, twisted in pairs), transmission speed on the local bus: 100 MBit/s, Extreme Condition variant, protection rating: IP20, incl. bus socket module and AxiolineF connectors

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > I/O

Additional Product Information

Key Commercial Data

Orderkey 2702464

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4055626459264

Weight per Piece (excluding packing) 144.000 g

Custom tariff number 85389091

Country of origin DE (Germany)

Dimensions

Dimensional drawing

Width 53.6 mm

Height 126.1 mm

Depth 54 mm

Note on dimensions The depth is valid when a TH 35-7,5 DIN rail is used (according to EN 60715).

Ambient conditions

Ambient temperature (operation) -25 °C ... 60 °C (Standard)

-40 °C ... 70 °C (Extended, see section "Tested successfully: use under extreme ambient conditions" in the data sheet.)

Ambient temperature (storage/transport) -40 °C ... 85 °C

Permissible humidity (operation) 5 % ... 95 % (non-condensing)

Permissible humidity (storage/transport) 5 % ... 95 % (non-condensing)

Air pressure (operation) 70 kPa ... 106 kPa (up to 3000 m above sea level)

Air pressure (storage/transport) 70 kPa ... 106 kPa (up to 3000 m above sea level)

Degree of protection IP20

Connection data

Designation Axioline F connector

Connection method Push-in connection

Note on the connection method Please observe the information provided on conductor cross sections in the "Axioline F: system and installation" user manual.

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 1.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 1.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 16

Stripping length 8 mm

General

Mounting type D...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AXL F UTH8 XC 1F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.