

INDUSTRIAL COMPONENT DATA

AXL P EX IS DO4 SD 21-60 1F 1087078 PHOENIX CONTACT

Axioline P, Digital output module, Digital outputs: 4, 2..

Brand: PHOENIX CONTACT | Manufacturer Part Number: AXL P EX IS DO4 SD 21-60 1F



Manufacturer	PHOENIX CONTACT
MPN / Reference	AXL P EX IS DO4 SD 21-60 1F
Catalog number	1087078
Category	Fieldbus, decentr. periphery - digital I/O module
Minimum order	1 Pcs
Document ID	EO-AC98587EB1
Generated	2026-08-03

Product Overview

Axioline P, Digital output module, Digital outputs: 4, 21 V, 60 mA, connection technology: 2 conductors, Magnetic activation, intrinsically safe, transmission speed on the local bus: 100 MBit/s, protection index: IP20, including bus socket module and male connector

Axioline P, Digital output module, Digital outputs: 4, 21 V, 60 mA, connection technology: 2 conductors, Magnetic activation, local bus transmission rate: 100 MBit/s, protection rating: IP20, including busy socket module male connector

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > I/O

Additional Product Information

ETIM for 1087078 PLC's (EC001599)

Feature Name

Feature Value

Voltage type (supply voltage) (EF002991)

DC

Number of digital inputs (EF001992)

0

Number of digital outputs (EF001993)

4

Digital inputs configurable (EF008516)

No

Digital outputs configurable (EF008520)

No

Type of voltage (input voltage) (EF003033)

DC

Type of digital output (EF003601)

None

Output current (EF003202)

0.06 A

Permitted voltage at output (EF007553)

21 V

Short-circuit protection, outputs available (EF003203)

No

Number of HW-interfaces industrial Ethernet (EF003020)

0

Number of interfaces PROFINET (EF006932)

0

Number of HW-interfaces RS-232 (EF003021)

0

Number of HW-interfaces RS-422 (EF003022)

0

Number of HW-interfaces RS-485 (EF003023)

0

Number of HW-interfaces serial TTY (EF003024)

0

Number of HW-interfaces parallel (EF003026)

0

Number of HW-interfaces wireless (EF006933)

0

Number of HW-interfaces USB (EF003025)

0

Number of HW-interfaces other (EF003027)

0

With optical interface (EF003028)

No

Radio standard Bluetooth (EF007178)

No

Radio standard WLAN 802.11 (EF007179)

No

Radio standard GPRS (EF008523)

No

Radio standard GSM (EF008524)

No

Radio standard UMTS (EF008525)

No

IO link master (EF007298)

No

System accessory (EF004118)

Yes

Degree of protection (IP) (EF005474)

IP20

Type of electric connection (EF003961)

Other

Time delay at signal change (EF002382)

0 ms

Fieldbus connection over separate bus coupler possible (EF004002)

Yes

Suitable for rail mounting (EF003972)

Yes

Wall mounting/direct mounting (EF0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AXL P EX IS DO4 SD 21-60 1F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.