

**INDUSTRIAL COMPONENT DATA**

# AXL P FBPS BASE 2316393 PHOENIX CONTACT Axioline P base for PROFIBUS PA power supply plugs. Provides redundancy..

Brand: PHOENIX CONTACT | Manufacturer Part Number: AXL P FBPS BASE



|                 |                                                            |
|-----------------|------------------------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                                            |
| MPN / Reference | AXL P FBPS BASE                                            |
| Catalog number  | 2316393                                                    |
| Category        | Fieldbus, decentr. periphery - power supply/segment module |
| Minimum order   | 1 Pcs                                                      |
| Document ID     | EO-DF0B371A1A                                              |
| Generated       | 2026-08-06                                                 |

## Product Overview

Axioline P base for PROFIBUS PA power supply plugs. Provides redundancy when two plugs are installed. Redundancy is maintained across multiple bases via backplane connectors.

Axioline P base for PROFIBUS PA power supply connector. Provides redundancy for the fieldbus power supply in case of installation of two plugs.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                       |
|--------------|-----------------------|
| Catalog path | PHOENIX CONTACT > I/O |
|--------------|-----------------------|

## Additional Product Information

Key Commercial Data

Orderkey 2316393

Packing unit 1 pc

Catalog page Page 99 (C-6-2019)

GTIN 4055626368375

Weight per Piece (excluding packing) 200.000 g

Custom tariff number 85366990

Country of origin US (United States)

Drawings

Dimensions

General

Serial interface

Classifications

Note

Ambient conditions

Power supply

Standards and Regulations

Drawings

Connection diagram

Application drawing

Application drawing

Block diagram

Dimensional drawing

Dimensional drawing

Dimensions with power supply plugs installed in base

[Back to top](#)Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

[Back to top](#)Dimensions

Dimensional drawing

Width 35 mm

Height 130 mm

Depth 125 mm

[Back to top](#)Ambient conditions

Ambient temperature (operation) -40 °C ... 65 °C (Mounting position: wall mounting on horizontal DIN rail)

-40 °C ... 50 °C (Mounting position: wall mounting on vertical DIN rail with up to four PROFIBUS PA segments (power supplies in redundant configuration))

Ambient temperature (storage/transport) -40 °C ... 85 °C

Permissible humidity (operation) 5 % ... 95 % (non-condensing)

Permissible humidity (storage/transport) 5 % ... 95 %

Altitude 2000 m (above sea level)

Degree of protection IP20

[Back to top](#)General

Net weight 198.9 g

Color gray

Degree of pollution 2

Overvoltage category II

[Back to top](#)Power supply

Supply voltage range 18.5 V DC ... 30.5 V DC

Max. current consumption 950 mA (18.5 V DC, 500 mA load)

Typical current consumption 750 mA ()

C...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AXL P FBPS BASE with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.